SCREENING SITE INSPECTION REPORT
FOR

WABASH PAPER COATINGS
WABASH, INDIANA
U.S. EPA ID: IND981961501
SS ID: NONE
TDD: F05-8802-004

PAN: FINO662SB

EPA Region 5 Records Ctr.

978241

OCTOBER 29, 1991



ecology and environment, inc.

111 WEST JACKSON BLVD., CHICAGO, ILLINOIS 60604, TEL 312-663-9415
International Specialists in the Environment
recycled paper

SIGNATURE PAGE
FOR
SCREENING SITE INSPECTION REPORT
FOR
WABASH PAPER COATINGS

WABASH, INDIANA U.S. EPA ID: IND981961501

SS ID: NONE TDD: F05-8802-004 PAN: FIN0662SB

Prepared	by:	Detrohysti	Date:	19/28/9)
		Deborah Epstein	_	
		FIT Team Leader		
		Ecology and Environment, Inc.		
Reviewed	by:	Michael Dieckhaus FIT Unit Manager	Date:	10-28-91
		Ecology and Environment, Inc.		
Approved	by:	Quality Quality	Date:	D/39/4/
		Jerome D. Oskvarek	-	7 7 7 7
	j	♥IT Office Manager		
	l	Ecology and Environment, Inc.		

TABLE OF CONTENTS

Section			Page
1	I N TR(DDUCTION	1-1
2	SITE	BACKGROUND	2-1
	2.1	INTRODUCTION	2-1
	2.2	SITE DESCRIPTION	2-1
	2.3	SITE HISTORY	2–1
3	SCRE	ENING SITE INSPECTION PROCEDURES AND FIELD	
	OBSE	RVATIONS	3-1
	3.1	INTRODUCTION	3-1
	3.2	SITE REPRESENTATIVE INTERVIEW	3-1
	3.3	RECONNAISSANCE INSPECTION	3-1
	3.4	SAMPLING PROCEDURES	3-4
4	ANAL	YTICAL RESULTS	4–1
5	DISC	USSION OF MIGRATION PATHWAYS	5-1
	5.1	INTRODUCTION	5–1
	5.2	GROUNDWATER	5-1
	5.3	SURFACE WATER	5-4
	5.4	AIR	5-5
	5.5	FIRE AND EXPLOSION	5-6
	5.6	DIRECT CONTACT	5–6
6	REFE	RENCES	6-1

Table of Contents (Cont.)

Appendix		Page
A	SITE 4-MILE RADIUS MAP	A-1
В	U.S. EPA FORM 2070-13	B-1
С	FIT SITE PHOTOGRAPHS	C-1
D	U.S. EPA TARGET COMPOUND LIST AND TARGET ANALYTE LIST QUANTITATION/DETECTION LIMITS	D-1
E	WELL LOGS OF THE AREA OF THE SITE	E-1

LIST OF FIGURES

Figure		Page
2-1	Site Location	2-2,
3–1	Site Features	3–3
3–2	On-Site Soil Sampling Locations	3-6
3–3	Off-Site Soil Sampling Location	3-7

LIST OF TABLES

Table	•	Page
2-1	Chemicals Used in the Coating Process	2-4,
4-1	Results of Chemical Analysis of FIT-Collected Soil Samples for the WPC Site SSI	4–2

1. INTRODUCTION

Ecology and Environment, Inc., Field Investigation Team (FIT) was tasked by the United States Environmental Protection Agency (U.S. EPA) to conduct a screening site inspection (SSI) of the Wabash Paper Coatings (WPC) site (aka Mafcote-Wabash Paper Coatings, Inc.) under contract number 68-01-7347.

The site was discovered by the Office of Solid and Hazardous Waste Management (OSHWM), Indiana Department of Environmental Management (IDEM), in October 1987. Allegations of sewer discharge high in metals and suspended solids by the Wabash Public Works as well as the old age and condition of the facility prompted IDEM to evaluate the site (Wonderly 1987).

The site was evaluated in the form of a preliminary assessment (PA) that was submitted to U.S. EPA. The PA was prepared by Mary Anne Hunter, OSHWM, IDEM, and is dated October 15, 1987 (U.S. EPA 1987).

FIT prepared an SSI work plan for the WPC site under technical directive document (TDD) F05-8802-004, issued on December 3, 1987. The SSI work plan was approved by U.S. EPA on March 26, 1991. The SSI of the WPC site was conducted on April 17, 1991, under amended TDD F05-8802-004, issued on March 26, 1991.

The FIT SSI included an interview with a site representative, a reconnaissance inspection of the site, and the collection of seven soil samples.

The purposes of an SSI have been stated by U.S. EPA in a directive outlining Pre-Remedial Program strategies. The directive states:

All sites will receive a screening SI to 1) collect additional data beyond the PA to enable a more refined preliminary HRS [Hazard Ranking System] score, 2) establish priorities among sites most likely to qualify for the NPL [National Priorities List], and 3) identify the most critical data requirements for the listing SI step. A screening SI will not have rigorous data quality objectives (DQOs). Based on the refined preliminary HRS score and other technical judgement factors, the site will then either be designated as NFRAP [no further remedial action planned], or carried forward as an NPL listing candidate. A listing SI will not automatically be done on these sites, however. First, they will go through a management evaluation to determine whether they can be addressed by another authority such as RCRA [Resource Conservation and Recovery Act].... Sites that are designated NFRAP or deferred to other statutes are not candidates for a listing SI.

The listing SI will address all the data requirements of the revised HRS using field screening and NPL level DQOs. It may also provide needed data in a format to support remedial investigation work plan development. Only sites that appear to score high enough for listing and that have not been deferred to another authority will receive a listing SI. (U.S. EPA 1988)

U.S. EPA Region V has also instructed FIT to identify sites during the SSI that may require removal action to remediate an immediate human health or environmental threat.

SITE BACKGROUND

2.1 INTRODUCTION

This section presents information obtained from SSI work plan preparation, the site representative interview, and the reconnaissance inspection of the site.


2.2 SITE DESCRIPTION

The WPC site consists of an active paper coating facility situated on an approximately 1 1/4-acre lot located at 410 South Carroll Street in Wabash, Wabash County, Indiana (SW1/4SW1/4NE1/4 sec. 14. T.27N., R.6E.) (see Figure 2-1 for site location). The site is located in a moderately populated area near the center of the city of Wabash. Land use in the immediate vicinity of the site is mixed industrial, commercial, and residential. The Wabash River is located approximately 1/4 mile south of the site.

A 4-mile radius map of the WPC site is provided in Appendix A.

2.3 SITE HISTORY

The WPC site is currently owned by Mafcote Industries (Mafcote) of Norwalk, Connecticut. Wabash Paper Coatings, Inc., of Wabash, Indiana, owned and operated the WPC site from 1965 until 1985, when Mafcote purchased the site and expanded the company name to Mafcote-Wabash Paper Coatings, Inc. (Mafcote-Wabash). Previous owners and operators of the site prior to 1965 include Ford Meter Box, a manufacturer of thermostats and metering devices; a foundry; a cabinet maker; and the city of



SOURCE: USGS, Wabash, IN Quadrangle, 7.5 Minute Series, 1963, photorevised 1981.




FIGURE 2-1 SITE LOCATION

Wabash. The exact dates of ownership and specific operations are not known (Evans 1991).

Mafcote-Wabash coats paper products such as tags with mixtures of Georgia clay, latex/polymer binders, and textile pigments comprised of metal oxides. Paper is only coated at the facility, not produced. The naturally occurring Georgia clay has a high zinc content and therefore is classified as a special waste that must undergo heavy metal treatment prior to disposal (Evans 1991). Chemicals such as latex/polymer binders, pigments, and brighteners that are used in the coating process at the WPC site are listed in Table 2-1.

Thirteen employees, working five days a week, perform the coating process. Paper stock is rolled through the coating mixture and then dried in a gas-fired infrared oven (Evans 1991). When a pigment color is changed, any excess coating mixture and pigment remaining from the previous coating process are pumped into a floor drain before a fresh pigment is used. The drain empties into a 5,000-gallon underground storage tank (UST) located on the south side of the paper coating building (Evans 1991). The exact date that this storage tank was installed or what material it is constructed of are not known. FIT file information indicates that proposed industrial waste treatment and disposal facilities for paper coating wastes at the WPC site were approved in March 1966 by the Indiana State Board of Health. The proposed facilities included a plan for a plant sewer, a holding tank, a 50-gallons-per-minute (gpm) diaphragm pump, and a tank trailer (Offutt 1966).

The contents of the 5,000-gallon UST are pumped into a treatment tank located inside the paper coating building where the coating waste, containing heavy metals, is treated and devatered with B-22 polymer, aluminum sulfate, and lime (Evans 1991).

After the coating waste is dewatered, the residual sludge is mixed with sawdust and stored in an outdoor 20-cubic-yard dumpster ælong with general refuse generated at the WPC site. The dumpster is removed bimonthly by Wabash Valley Refuse Removal, at which time its contents, including 6 1/4 cubic yards of treated sludge, is disposed of at Wabash Valley Landfill (IDEM 1991). Approval for the disposal of the sludge/

Table 2-1

CHEMICALS USED IN THE COATING PROCESS

CHEMICALS

Aqua Ammonia-26 Degrees
Hydrasperse Clay-Organic
Pro-Cote 150 Protein-Organic
Hydrocarb 30-Calcium Carbonate
Ti-Pure-LW Titanium Dioxide
Rhoplex P-554-Aqueous Acrylic Emulsion
Rhoplex B-85-Aqueous Acrylic Emulsion
Foamaster 1407-Calcium Stearate
Foamaster C-104 Calcium Stearate
Vitrofoss-Sodium Hexametaphosphate
Latex-2149-Resin Emulsion

COLORS

Permanent Violet
Phthalo Blue
Aqua Black
Red-BL
Aquafine Green-B
Aquafine Orange-RB
Yellow P-2G
* Copper Phthalozyanine
Naphthol
Diaralid Yellow

Source: Evans 1991.

refuse waste by OSHWM, IDEM, requires that mo freestanding liquids be dumped into the Wabash Valley Landfill (Evams 1991).

In July 1988, Edglo Laboratories, Inc. (Edglo), of Fort Wayne, Indiana, conducted a one-time Extraction Procedure (EP) Toxicity test on a treated coating waste sample (Knott 1988). The coating waste was analyzed for arsenic, barium, cadmium, chromium, lead, mercury, selenium, silver, and zinc. Edglo found that the treated coating waste sample did not contain levels of analytes considered hazardous according to EP Toxicity levels (Knott 1988).

Mafcote-Wabash discharges the wastewater generated during the dewatering treatment process to the city sever. Problems with sever discharges high in solids and metals were alleged in previous years and brought to the attention of IDEM (U.S. EPA 1987). However, FIT files have no documented evidence of any violations regarding sever discharge. According to a schedule of compliance with the city of Wabash industrial wastewater treatment program, Mafcote-Wabash currently monitors wastewater that is discharged to the city sever twice per year (Evans 1991). The most recent wastewater analysis available at the time of the SSI was performed by Edglo, and levels of metals in the wastewater were found to be below EP Toxicity levels.

The only remedial activity known to have taken place at the WPC site was a one-time-only asbestos removal conducted in September 1985 when Mafcote first purchased the site. The State of Indiana Environmental Management Board approved the removal of 55, 55-gallon bags of asbestos from a water pipe inside the facility by Asbestos Removal, Inc., of Wabash, Indiana, which disposed of the asbestos at the Spring Valley Landfill in Wabash, Indiana (Pickard 1985).

No further remedial action has taken place at the WPC site.

3. SCREENING SITE INSPECTION PROCEDURES AND FIELD OBSERVATIONS

3.1 INTRODUCTION

This section outlines procedures and observations of the SSI of the WPC site. Individual subsections address the site representative interview, reconnaissance inspection, and sampling procedures. Rationales for specific FIT activities are also provided. The SSI was conducted in accordance with the U.S. EPA-approved work plan.

The U.S. EPA Potential Hazardous Waste Site Inspection Report (Form 2070-13) for the WPC site is provided in Appendix B.

3.2 SITE REPRESENTATIVE INTERVIEW

Deborah Epstein, FIT team leader, conducted an interview with Daryl Evans, Operations Manager, Mafcote-Wabash. Also present at the interview were Mary Tierney and Mikhail Gumin, FIT team members. The interview was conducted on April 17, 1991, at 9:20 a.m. in Evans's office at Mafcote-Wabash, 410 South Carroll Street, Wabash, Indiana. The interview was conducted to gather information that would aid FIT in conducting SSI activities.

3.3 RECONNAISSANCE INSPECTION

Following the site representative interview, FIT conducted a reconnaissance inspection of the WPC site and surroumding area in accordance with Ecology and Environment. Inc. (E & E), health and safety guidelines. The reconnaissance inspection began at 12:10 p.m. and included a walk-through of the site to determine appropriate health and safety requirements for conducting on-site activities and to make

observations to aid in characterizing the site. FIT also determined sampling locations during the reconnaissance inspection. FIT was accompanied by Evans during the reconnaissance inspection.

Reconnaissance Inspection Observations. The WPC site includes two interconnected buildings, covering approximately 15,000 square feet on the northeastern portion of the 1 1/4-acre site. The site is bordered by Conrail Railroad tracks on the north, West Street on the south, Carroll Street on the east, and a manufacturing company on the west (see Figure 3-1 for site features). The topography of the site is generally level.

The immediate vicinity of the site consists of residences to the south and east, and industrial and commercial properties to the north and west.

There are two on-site brick buildings, an office/paper coating building and a warehouse, which are connected by a two-story aluminum walkway that is also used for storage of paper stock and coated paper cores. A drum storage shed and a maintenance shed are attached to the northern portion of the L-shaped paper coating building on the west side.

The drum storage shed is enclosed by three aluminum sides and a roof. The side of the shed facing south is open. Approximately 60, 55-gallon drums were observed inside the shed, which has a dirt floor. Most of the drums appeared to be empty. Several drums were labeled as flammable liquids such as paper protector and oil. Ten drums were observed next to the storage shed. A small patch of a crusty yellow substance resembling hardened epoxy was observed next to one of the 10 drums. Areas of dead grass were also observed near the drums stored outside the shed. A parking area is located adjacent to the drum storage shed.

Rusted metal and wooden scraps were observed next to the maintenance shed, which was undergoing roof repair at the time of the SSI.

A gravel access road extends west from Carroll Street near the southeast corner of the site, between the warehouse and West Street, then turns north and continues along the west side of the paper coating building to the drum storage shed. Approximately nine empty 55-gallon




FIGURE 3-1 SITE FEATURES

drums that once contained pigment were observed at the southwest corner of the paper coating building, next to the gravel access road.

The 5,000-gallon UST is located between the two buildings, just west of the connective walkway. A pipe, attached to wooden stakes approximately 3 feet above the ground, leads from the cover of the UST to the waste treatment tank located inside the southwest corner of the paper coating building. An aboveground vent is located next to the UST cover. FIT observed a patch of stressed vegetation between the UST cover and the aboveground vent. During the SSI, a thick green-colored liquid, which was being drained from the paper coating building into the UST, flooded the ground surrounding the aboveground vent. Employees, alerted by FIT to the flooding, unclogged the vent and poured sawdust on the ground to soak up the green-colored liquid.

Two overturned empty tanks, a sawdust pile, and a 20-cubic-yard refuse/sludge dumpster are located approximately 20 feet west of the UST cover. At the time of the SSI, the dumpster was filled with sludge mixed with sawdust, scraps of paper, cardboard cores, and empty pigment drums. FIT observed that the dumpster was leaking, forming a puddle of pink and green-colored liquid at the north end of the dumpster. Patches of black-stained and stressed vegetation were observed in several areas next to the dumpster and the UST.

Several piles of wooden pallets were located on the west side of the gravel access road. Also, two semitrailers were stored approximately 75 feet southwest of the wooden pallets, near the edge of the west boundary of the site. Several areas of concrete were observed near the semitrailers. Blackened soil and stressed vegetation were observed next to the semitrailers and in various places north of the semi-trailers.

FIT photographs from the SSI of the WPC site are provided in Appendix C.

3.4 SAMPLING PROCEDURES

: 3

Samples were collected by FIT at locations selected during the reconnaissance inspection to determine whether U.S. EPA Target Compound List (TCL) compounds or Target Analyte List (TAL) analytes were present

at the site. The TCL compounds and TAL analytes are included with corresponding quantitation/detection limits in Appendix D.

On April 17, 1991, FIT collected seven surface and subsurface soil samples, including one potential background sample. The site representative accepted offered portions of the FIT-collected samples.

Soil Sampling Procedures. Surface soil sample 51 was collected from an area of blackened soil and stressed vegetation located approximately 15 feet southeast of the cover of the UST (see Figure 3-2 for on-site soil sampling locations). Surface soil sample S2 was collected from an area of stressed vegetation next to the UST cover. Soil samples S1 and S2 were collected to characterize the soil that may be exposed to untreated coating waste overflowing or leaking from the vent and pipes leading to the UST.

Surface soil sample S3 was collected from soil in a puddle of pink and green-colored liquid that was observed leaking from the northern edge of the refuse/sludge dumpster during the SSI. Sample S3 was collected in order to characterize the soil beneath the dumpster.

Surface soil sample S4 was collected beneath the layer of crusty, yellow substance that may have leaked from 55-gallon drums stored outside the south side of the drum storage shed. This sample was collected to determine whether chemicals that were once contained in the drums may have leaked into the soil.

Subsurface soil sample S5 was collected at an approximate depth of 2 1/2 feet, from an area of blackened soil and stressed vegetation located approximately 50 feet west of the parking area. An attempt to collect a deeper sample was hindered by the presence of hard rock below 2 1/2 feet. Surface soil sample S6 was collected from an area of stressed vegetation located approximately 20 feet south of the semitrailers. Samples S5 and S6 were collected to determine whether TCL compounds and TAL analytes were present in their respective locations.

Surface soil sample S7 was collected as a potential background sample from an approximately 30-foot-high, grass- and tree-covered hill located in a residential area on the south side of the Wabash River, approximately 2,100 feet southwest of the WPC site at 184 Middle Street (see Figure 3-3 for off-site soil sampling location). The potential




FIGURE 3-2 SOIL SAMPLING LOCATIONS



SOURCE: USGS, Wabash, IN Quadrangle, 7.5 Minute Series, 1963, photorevised 1981.




FIGURE 3-3 OFF-SITE SOIL SAMPLING LOCATION

background sample was collected to determine the representative chemical content of the soil in the vicinity of the site.

All surface soil samples—S1, S2, S3, S4, S6, and S7—were collected with stainless steel trowels. Subsurface soil sample S5 was collected with a posthole digger. The sample portions collected for volatile organic analysis were transferred directly to sample bottles with a stainless steel spoon. The remaining sample portions were placed into a stainless steel bowl, mixed, and then transferred to the appropriate sample bottles, using a stainless steel spoon or a hand trovel (E & E 1987).

Standard E & E decontamination procedures were adhered to during the collection of all seven soil samples. The procedures included the scrubbing of all equipment (e.g., spoons, trowels, bowls, and posthole digger) with a solution of detergent (Alconox) and distilled water, and triple-rinsing the equipment with distilled water before the collection of each sample (E & E 1987). All seven soil samples were packaged and shipped in accordance with U.S. EPA-required procedures.

As directed by U.S. EPA, all seven soil samples were amalyzed using the U.S. EPA Contract Laboratory Program (CLP).

4. ANALYTICAL RESULTS

This section presents results of the chemical analysis of soil samples collected by FIT during the SSI of the VPC site. All samples were analyzed for volatile organics, semivolatile organics, pesticides/polychlorinated biphenyls (PCBs), metals, and cyanide. Complete chemical analysis results of FIT-collected soil samples are provided in Table 4-1. In addition, significant tentatively identified compounds (TICs) detected in the analysis of FIT-collected samples are also provided in Table 4-1.

Quantitation/detection limits used in the analysis of FIT-collected samples are provided in Appendix D.

The analytical data from the chemical analysis of FIT-collected samples for this SSI have been reviewed under the direction of U.S. EPA for validity; the review has been approved by U.S. EPA. The analytical data have also been reviewed by FIT for usability. Any additions, deletions, or changes resulting from review of the data have been incorporated in the chemical analysis results table presented in this section.

Table 4-1 RESULTS OF CHEMICAL ANALYSIS OF FIT-COLLECTED SOIL SAMPLES FOR THE WPC SITE SSI

Sample Collection Information	Sample Number						
and Parameters	s1	S2	S3	S4	s 5	S 6	57
Date	4/17/91	4/17/91	4/17/91	4/17/91	4/17/91	4/17/91	4/17/9:
Time,	1330	1340	1330	1407	1520	1452	164
CLP Organic Traffic Report Number	EKN21	ENA49	ENA50	ENA51	EMW9 2	EMW93	EMW9
CLP Inorganic Traffic Report Number	MEMG76	. MEMG77	MEMG78	MEMG79	MEMG80	MEMG81	MEMG8
Compound Detected							
(values in µg/kg)							
Volatile Organics							
methylene chloride				~~		7	
scetone		27	57,000	***			
2-butanone (MEK)		•	1,500J				
toluene				~-	7	5J	
Semivolatile Organics							
naphthalene	<u>-</u>				320Ј		
2-methylnaphthalene				2,500J	400J		
acenaphthene					90J		
dibenzofuran					160J		
hexachlorobenzene						51 <i>J</i>	
phenanthrene		120 <i>J</i>			740		
anthracene					130Ј		
di-n-butylphthalate							510
:luoranthene	22		2110		120J		
pyrene		160J			1,600	74J	
penzo[a]anthracene					700 <i>3</i>		
chrysene				•	890		
ois(2-ethylhexyl)phthalate	3107	370J		~-			1903
Denzo(b]fluoranthene	240J				2,000		
oenzo(a)pyrene	210J			~-	810		

Table 4-1 (Cont.)

Sample Collection Information	Sample Number						
and Parameters	S1	· s2	S 3	S4	s 5	S6	s7
ndeno[1,2,3-cd]pyrene					240J		
Pesticides/PCBs							
Aldrin			***		11		
Aroclor 1248						410	
Aroclor 1254				1,700			-
PICs+							
penzenesulfonamide, 4-methyl (70-55-3)			30,000J				
lH-benzo[a]fluorens	==				1,000J		
(238-84-6)					2,000		
penzo[e]pyrene (192-97-2)		· 			3,000J		
Analyte Detected							
(values in mg/kg)							
luminum	5,200	12,900	11,400	3,230	4,110	25,800	14,700
ntimony	231N*J	R	R	R	R	11.0BN*J	
reenis	7.63	6.05	7.23	39.13	0.03	19.73	10.9J
arium	33.9	204	63.8	132	68.8	24.7B	80.5
eryllium	0.37B	0.718	0.42B	0.59B		0.79B	0.79В
admium	20.4N*J	8.4N*J	8.4N*J	42.6N*J	6.9N*J	12.3N*J	6.6N*3
alcium	8,300*	18,100*	84,900*	19,300*	35,000*	2,000*	27,900*
hromium	7.1N*J	179N*J	45.3N*J	123N*J	7.0N*J	105N*J	29.6N*3
obalt	14.1	8.5B	5.5B	14.9	5.0B	4.0B	10.6B
opper	168,000*J	192*J	1,340*J	1,540*J	144*J	1,500*J	28.4*3
ron	20,900*J	25,600*J	15,600*J	181,000*J	25,100*J	10,900*J	22,100*3
ead	9,170*J	1,370*J	258*J	595*J	131*J	7,760*J	78.2*3
agnesium	2,820	7,570	21,900	2,540	6,910	1,120B	5,810
anganese	213	570	358	1,400	325	274	606
ercury		0.16NJ	0.98NJ	1.0NJ		0.18NJ	0.13N
ickel	942*J	21.3*J	35.3*J	43.2*J	13.5*J	60.9*J	21.9*3
otass1um	5478	1,470	ត១១២	520n	534n	128B	2,100
elenium	0.52B	0.65BWJ	0.67в	0.86B	0.58B	1.7	0.49B

Commence of the Anna Anna Anna Anna

Table 4-1 (Cont.)

Sample Collection Information				Sample Number			
and Parameters	S1	52	S3	S4	' s5	S 6	s7
silver	13.2N*J	R	R	R	R	R	R
odium	211BJ	157BJ	490B	144BJ	178BJ	370B	99.1BJ
challium	0.48BWJ		~-	0.46BWJ	0.36в	1.18	0.55B
vanadium	17.6	26.4	11.1B	67.5	12.6	15.9	30.0
inc	31,600*J	360*J	845*J	635*J	159*J	4,740*3	113*J
cyanide			~~	0.97	~-		

⁻⁻ Not detected.

[†] TIC Chemical Abstracts Service (CAS) numbers, if available, are provided in parentheses.

R

COMPOUND QUALIFIER DEFINITION

protocols.

INTERPRETATION

Analyte value is not usable.

L.	Indicates an estimated value.	Compound value may be semiquantitative
ANALYTE QUALIFIERS	DEFINITION	INTERPRETATION
N	Spike recoveries outside QC protocols, which indicates a possible matrix problem. Data may be biased high or low. See spike results and laboratory narrative.	Value may be quantitative or semi- quantitative.
*	Duplicate value outside QC protocols which indicates a possible matrix problem.	Value may be quantitative or semiquantitative.
В	Value is real, but is above instrument DL and below CRDL.	Value may be quantitative or semi- quantitative.
J	Value is above CRDL and is an estimated value because of a QC protocol.	Value may be semiquantitative.
W	Post-digestion spike for furnace AA analysis is out of control limits (35-115%), while sample absorbance is <50% of spike absorbance.	Value may be semiquantitative.

Results are unusable due to a major violation of QC

5. DISCUSSION OF MIGRATION PATHWAYS

5.1 INTRODUCTION

This section presents discussions of data and information pertaining to potential migration pathways and targets of TCL compounds and TAL analytes that are possibly attributable to the WPC site.

The five migration pathways of concern discussed are groundwater, surface water, air, fire and explosion, and direct contact.

5.2 GROUNDWATER

In accordance with the U.S. EPA-approved work plan, groundwater samples were not collected during the SSI of the WPC site. TCL compounds were detected in on-site soil samples, including acetone (57,000 µg/kg in sample S3), benzo[b]fluoranthene (2,000 µg/kg in sample S5), 2-methylnaphthalene (2,500J µg/kg in sample S4), pyrene (1,600 µg/kg in sample S5), and the PCB Aroclor 1254 (1,700 µg/kg in sample S4).

TAL analytes were also detected in on-site soil samples including antimony (231N*J mg/kg), copper (168,000*J mg/kg), lead (9,170*J mg/kg), nickel (942*J mg/kg), and zinc (31,600*J mg/kg) in sample S1; and cyanide (0.97 mg/kg) and mercury (1.0NJ mg/kg) in sample S4.

In addition, several TICs were detected in on-site soil samples including benzo[e]pyrene (3,000J μ g/kg in sample S5), 11H-benzo[a]-fluorene (1,000J μ g/kg in sample S5), and benzenesulfonamide, 4-methyl (30,000J μ g/kg in sample S3) (see Table 4-1 for definition and interpretation of the J qualifier).

The TCL compounds and TAL analytes detected in on-site soil samples are attributable to the site based on the following reasons.

- They were detected at levels above those of the background soil sample.
- TAL analytes were detected in surface soil sample S1, which was collected from an area where untreated coating waste was observed flowing onto the ground surface during the SSI.
- TCL compounds and TAL analytes were detected in soil samples collected near stressed vegetation and drums.
- The TCL compound acetone is a common constituent of the latex binders/polymers used in the coating process (E & E 1989).
- Heavy metals are constituents of the coating waste generated at the WPC site. The textile pigments used in the coating process contain metal compounds such as copper phthalozyanine (see Table 2-1) (Evans 1991).
- The Georgia clay used as the primary component in the coating mixture has a high zinc content (Evans 1991).

The potential exists for TCL compounds and TAL analytes detected in on-site soil samples to migrate to groundwater in the vicinity of the site, based on the following information.

 Mafcote-Wabash is currently using a 5,000-gallon UST to hold coating waste containing heavy metals prior to treatment (Evans 1991). The structural composition and condition of the UST are not known.

- During the SSI, FIT observed coating waste overflowing from an aboveground vent and cover of the UST onto the ground.
- During the SSI, FIT observed the open dumpster containing treated coating waste sludge leaking a liquid onto the ground surface.

The potential for TCL compounds and TAL analytes detected in onsite soil samples to migrate to groundwater in the vicinity of the site is also based on the geology of the area.

Glacial geology in the vicinity of the site is a result of Pleistocene-age Wisconsinan glaciation and consists of unconsolidated valley-train deposits of clay-rich till, gravel, sand, and silt. Till deposits north of the WPC site also include some ground moraine ice-contact stratified drift. Recent alluvial deposits of silt, sand, and gravel of the Martinsville Formation are present along the Wabash River (Indiana Department of Natural Resources [IDNR] 1971). Glacial geology south of the site and parallel to the Wabash River is part of the buried valley system known as the Teays Buried Valley (IDNR 1985). Bedrock in the vicinity of the WPC site is composed of Silurian-age limestone that forms the Liston Creek Limestone Member (IDNR 1971).

Area well logs indicate that glacial deposits range in thickness from approximately 3 feet to as much as 200 feet in the Teays Buried Valley, which is located approximately 2 1/2 miles south of the site. A well log for a well located directly west of the VPC site indicates that glacial deposits are approximately 31 feet in thickness (see Appendix E for well logs of the area of the site).

According to area well logs, the unconsolidated sand and gravel deposits and the limestone bedrock beneath the site each form an aquifer that is used for drinking water within a 3-mile radius of the VPC site. Municipal wells and some private wells draw drinking water from the sand and gravel deposits at depths ranging from 20 to 45 feet. Other private wells are set in and draw drinking water from the limestone unit at depths between 30 and 68 feet.

The area well logs also indicate the presence of impermeable clay layers within the unconsolidated deposits. However, these clay layers

are not laterally continuous within a 3-mile radius of the site. Therefore, the glacial drift aquifer is hydraulically connected to the bedrock aquifer and together they form a single aquifer of concern (AOC). The well log for an industrial well located 1/4 mile from the WPC site indicates that depth to the AOC is approximately 23 feet. The nearest drinking water well is located approximately 1 mile from the site.

Groundwater flow in the area is complex because of the hydraulic connection between the glacial drift and bedrock aquifers. However, flow through the unconsolidated deposits of the Wabash River floodplain is believed to be south toward the Wabash River (Clarke 1980).

The city of Wabash is served by the Indiana Cities Water Corporation municipal water system and obtains water from two well fields. One well field is located approximately 1 1/2 miles southeast of the site, approximately 2,000 feet east of Union Chapel Road, and consists of seven wells ranging in depth from 60 to 67 feet which draw from the sand and gravel glacial deposits (Heiner 1991). The second well field is located just over 3 miles southwest of the site, west of Yankee Road, and consists of two wells with depths of 187 feet and 203 feet, which draw from the Teays Buried Valley glacial deposits (Heiner 1991).

Water from the two well fields is blended before distribution and is supplied to all residents living within the corporate boundaries of the city of Wabash (Heiner 1991). Approximately 12,150 persons living within the city limits of Wabash are served by the municipal water system (Heiner 1991). In addition, approximately 850 persons are served by private wells screened in the AOC. The population using private wells was determined by counting the number of houses (308) within a 3-mile radius of the WPC site, but outside Wabash municipal water boundaries, on United States Geological Survey (USGS) topographic maps and multiplying that figure by 2.76, the persons-per-household average for Wabash County (U.S. Bureau of the Census 1982; USGS 1963, 1963a, 1969, 1969a). Therefore, the total potential target population is 13,000 persons.

5.3 SURFACE WATER

The surface water body most likely to be affected by the migration of TCL compounds and TAL analytes from the site is the Wabash River,

which flows from east to west approximately 1,500 feet south of the WPC site. However, a potential does not exist for TCL compounds and TAL analytes to migrate to surface water based on the following information.

- The intervening terrain between the site and the river has a downward slope of only approximately 1% (USGS 1963, 1963a, 1969, 1969a).
- FIT did not observe any drainage pathways leading from the site to the river.

The Wabash River is not used as a source of drinking water within 3 miles downstream of the site. The Wabash River is used for recreation, including fishing and boating, near the WPC site (Payne 1988).

5.4 AIR

A release of TCL compounds or TAL analytes to the air was not documented during the SSI of the WPC site. During the reconnaissance inspection, FIT site-entry instruments (OVA, explosimeter, and colorimetric monitoring tubes for hydrogen cyanide) did not detect levels that deviated from background concentrations at the site. In accordance with the U.S. EPA-approved work plan, further air monitoring was not conducted by FIT.

A potential does exist for TCL compounds and TAL analytes to migrate from the site via windblown particulates, based on the following information.

- TCL compounds and TAL analytes were detected in on-site surface soil samples at concentrations above background.
- No natural or man-made wind barriers exist on-site.
- The ground near a dumpster containing sludge and a UST holding coating waste is only partially covered by vegetation. The grass is either stressed or dead in most of the area.

Sawdust is mixed with coating waste sludge possibly containing heavy metals and is stored in an open dumpster on-site. The sawdust particles may become airborne and migrate off-site.

The population within a 4-mile radius of the site potentially affected by a release of TCL compounds and TAL analytes to the air is approximately 16,612 persons. This population includes the population of the city of Wabash (12,985) and the number of persons living outside the city limits but within a 4-mile radius of the site. The number of persons living outside the city limits was calculated by counting houses (1,314) within a 4-mile radius of the site on a USGS topographic map (USGS 1963, 1963a, 1969, 1969a) and multiplying this number by a persons-per-household value of 2.76 (U.S. Bureau of the Census 1982).

5.5 FIRE AND EXPLOSION

According to federal, state, and local file information reviewed by FIT, and an interview with Mike McMullet, Fire Chief, Wabash Fire Department, no documentation exists of an incident of fire or explosion at the site (McMullet 1990). According to FIT observations and site-entry equipment readings, no potential for fire or explosion existed at the site at the time of the SSI.

5.6 DIRECT CONTACT

According to federal, state, and local file information reviewed by FIT, observations made during the SSI, and the interview with the site representative, no incidents of direct contact with TCL compounds or TAL analytes at the WPC site have been documented.

A potential exists for direct contact with TCL compounds or TAL analytes detected on-site based on the following information.

- TCL compounds and TAL analytes were detected in surface soil samples at concentrations above background.
- The site is currently active.

- There are no natural boundaries, fences, or other security measures to restrict access to the site.
- The site is located in a mixed residential, commercial, and industrial area, with residences located less than 500 feet from the site.

The population within a 1-mile radius of the site potentially affected through direct contact with TCL compounds and TAL analytes at the site is approximately 6,000 persons. This population was calculated by using a planimeter to determine the portion of the population that resides within the city limits of Wabash and within a 1-mile radius of the site. In addition, approximately 13 persons are employed at the WPC site.

REFERENCES

. 3

ز..

- Clarke, Douglas, 1980, Editor, Governor's Water Resources Study Commission, State of Indiana, The Indiana Water Resource, Availability, Uses, and Needs, INDR.
- E & E, 1987, Quality Assurance Project Plan Region V FIT Conducted Site Inspections, Chicago, Illinois.
- ______, January 20, 1989, interoffice memorandum, to FIT staff, Re:
 wastes--paint and coating manufacture and use, prepared by
 Analytical Services.
- Evans, Daryl, April 17, 1991, Operations Manager, Mafcote-Wabash, interview, conducted by Deborah Epstein of E & E.
- Heiner, Boyd, July 8, 1991, District Supervisor, Indiana Cities Water Company, Wabash, Indiana, telephone conversation, contacted by Deborah Epstein of E & E.
- IDEM, March 22, 1991, OSHWM, Special Waste Disposal Notification, for waste generated by Mafcote-Wabash and transported by Wabash Valley Refuse Removal.
- IDNR, 1971, Indiana Geological Survey, Map of Bedrock and Unconsolidated Deposits, Regional Geologic Map No. 5, Muncie Quadrangle, prepared by A. M. Burger, J. L. Forsyth, R. S. Nicoll, and W. J. Wayne.

- Knott, Paul E., July 1, 1988, Assistant General Manager, Edglo, letter, to Daryl Evans, Operations Manager, Mafcote-Wabash, Re: analytical results of the EP Toxicity Test on a coating waste sample.
- McMullet, Michael, February 28, 1990, Fire Chief, Vabash Fire

 Department, Wabash Indiana, telephone conversation, contacted by

 Evelyn Mays of CCJM.
- Offutt, A. C., M.D., March 30, 1966, State Health Commissioner, Indiana State Board of Health, letter, to Milton Barnett, Jr., Wabash Paper Coatings, Inc., Wabash, Indiana, Re: industrial waste disposal facilities at Wabash Paper Coatings, Inc.
- Payne, Joe, August 5, 1988, Streams and Trails Section Head, IDNR,
 Department of Parks and Recreation, Indianapolis, Indiana,
 telephone conversation, contacted by Ron Short of E & E.
- Pickard, Ralph, September 26, 1985, Technical Secretary, IDEM, letter, to Cecil Dunn, Operator, Spring Valley Landfill, Vabash, Indiana, Re: disposal of asbestos pipe insulation from Vabash Paper Coatings, Inc., Vabash, Indiana.
- U.S. Bureau of the Census, 1982, 1980 Census of Population, Characteristics of the Population, General Population Characteristics,
 Indiana, Washington, D.C.
- U.S. EPA, 1987, <u>Potential Hazardous Vaste Site Preliminary Assessment</u>, for the WPC site, U.S. EPA ID: IND981961501, prepared by Mary Anne Hunter, OSHVM, IDEM.

Response, Pre-Remedial Strategy for Implementing SARA, Directive number 9345.2-01, Washington, D.C.

USGS, 1963, photorevised 1981, Rich Valley, Indiana Quadrangle, 7.5
Minute Series: 1:24,000.

_______, 1963a, photorevised 1981, Wabash, Indiana Quadrangle, 7.5
Minute Series: 1:24,000.

______, 1969, Peoria, Indiana Quadrangle, 7.5 Minute Series: 1:24,000.

_______, 1969a, Somerset, Indiana Quadrangle, 7.5 Minute Series: 1:24,000.

Wonderly, John, October 5, 1987, Public Works, Wabash, Indiana, telephone conversation, contacted by Mary Anne Hunter, OSHWM, IDEM, Re: Mafcote-Wabash waste.

7185:9

APPENDIX A

SITE 4-MILE RADIUS MAP

$SDMS\ US\ EPA\ Region\ V$

Imagery Insert Form

Some images in this document may be illegible or unavailable in SDMS.

Please see reason(s) indicated below:

Unless otherwise noted	or RESOLUTION variations. I, these pages are available in monochrome. The source document parages. The original document is available for viewing at the Superf Specify Type of Document(s) / Comments:
	is highly sensitive information. Due to confidentiality, materials with ailable in SDMS. You may contact the EPA Superfund Records Man
Unscannable Material:	
SDMS	Format. g equipment capability limitations, the document page(s) is not avail Specify Type of Document(s) / Comments:

APPENDIX B

U.S. EPA FORM 2070-13

•					
OFDA	POTENTIAL HAZARDOUS WASTESITE				TECATION IL OR STEHASOR
\$EPA	•	SITE INSPECTION F LOCATION AND INSPE		1/4/	
& SITE HAVE AND LOCATION					
M BITE MUE Rope among a companion	AKA Mof	core-weess	LT, NOUTE HO_ON SPECI		A
Wabash Paper Coati	ng tep	er Coatings 41		St,	prograf a co-c
Wabash		IN	46992	Wabash	164 05
	<u>49755.</u>	THEO OMEGGEOGIA BAMNATE O 8.6 DF.ORGR	EDERALO	C. STATE DO.COU	
IL INSPECTION DIFORMATION OF DATE OF PERFECTION (02)	ETE STARS	E) YEARS OF OPERATION			
4,17,91	D NICINE	1965	en porgren		MM
OLICO CITETY CHANGE POPECTOLO		C A A B B B B B B B B B B			
DADA BEDACONTRUCTO DESTATE DESTATECONTRU	CFOR		other Dotal	CHAL CONTRACTO	
SO OF REFERIOR		04 mile		OT ORGANIZATION	CHESTICAL C
Deborah Epstein	<u> </u>	Civil Engin	1991	EEE	प्रता ६६३ नेपाउ
Scott Turek		Creologist		E É E	(3/51863-8A12
Mary Tierney	<u> </u>	Biologist		EĘE	(3)21663-9415
Michael Die	eckhays	Biologist	·	EÉE	B12163-9415
Patrick Soderbe	49	Botanis	<u> </u>	E&E.	0121663-9415
Mikhail Gum	U,	Mechanica	Engineer	E&E	13121663-9415
13 STEREPESENTATIVES INTERVENE	3)	14 TIRE	15ACORESS		STAR SCOOL
Daryl Evans		Operations I'lang	Wabash, Ind	roll.St	1211 563-418
			Wabash, Lad	1010 46712	()
		•		-	. ()
	- -			- : - :	1 12
				•	()
					()
	-				· · · · · · · · · · · · · · · · · · ·

Partly sunny ~67° F

M. BEFORMATION AVAILABLE FROM

TORMOTE

Hally Atkinson

TOEM SHWM

Ochorah Epstein

CPA-FIT Ecology & (312) 663-9415

TOEM HALLOWNER

Environment

Ochorah Epstein

EPAFOR42070-13 (7-41)

<u>O</u> ,	FI	ΟΔ
V		

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 2-WASTE INFORMATION

E DENTIFICATION
ON STATE OF STITE PLACES
IN 098176/501

VLI	<i>/</i> \	1	PART 2-WASTE	ENFORMATION		10 10	16/301
L WASTE ST	ATES, QUANTITIES, AM	D CHURACTERIS	nes				•
	IATES purchased	OR WASTE OUWOIT		03 WASTE CHARACTE	MIC DOWN		
O A SOLO # A POWCE # C SLICCE O D OTI€A		10 05 DAMY 78	waknowa 5 14 gd 3 Linon nknown	W.A. TOUC VII B. COMPOS O.C. RADON Holy YEO PERSSI	CTIME THE RULE	HOLE DEPLOS	ne Larene Larene
IL WASTE T	YPE	<u>. </u>					
CATEGORY	2.6SINCE	w€ ;	Deutowa 22040 10	DE CHALLO IN SOLD SO	esees (
SU	SLUCCE		61/4	yd³	bimonthly -	treated conting	المحيا
OLW	DLYWASTE			4		Slugge	WAY TO
so.	SOLVENTS		un known				
PS0	PESTICOES		Stee Perily and				
000	OTHEROGENICO	HEMONS	MAKAOWA				
100	NORGWCO-®		WALAGUA		cyanide, (AH	delected in So.	Se coles
160	ACOS		VIA PREVI			7 00.00 12, 50.	- 30/1/45
BAS	BASES					h31	
MES	HEAVY WELKS		UNKAOWA	ļ ———	OG TO THE REAL PROPERTY OF THE PARTY OF THE	generated by	Tare Come
	DOUS SUBSTANCES &	Annah brand basar			desters	n Soil sample	62
O1 CATEGORY	Y		63CUSHU-BER	04STONGEOS		esco-computor	CO-COMPANDO
		-					Two controls
	 					 	}
			4-1 And				
					· ····································		
					-		
						· · · · · ·	
}	1		1	1	•	3	
	1:	<u>:</u>	1 :	1		-	1
		·					<u> </u>
V. FEEDS	TOCKS parameters	~~					
CATEGO	MY 01 FEEDS	COCHE	et CASHAMER	CATEGORY	ON PEEDS	TOCKINA	et CAS KA
FOS	Georgia	Clay	unknow^	FDS			
FOS				FOS			
FOS	See section	on 2, Tabl	02-1	FDS			
FOS			<u> </u>	FOS			
	CES OF INFORMATION			· ··········			
	FIT sik inspe						
	State and	भग मध	ποινιστι	10/	•		
L							

EPAFORM 2010-13(7-4%)

	POTENT	IAL HAZARDOUS WASTESITE	ETHER J	CATION
SEPA	sn	TE INSPECTION REPORT	1101 10	98/961501
VLIII	PART 3-DESCRIPTION	OF HAZARDOUS CONDITIONS AND INCOENT	s Live IV	101121301
	TIONS AND INCIDENTS			
A CACUNOWATE	maly affected: ~ 13,	02 OBSERVED (DATE:	POTENTAL	D WTECED
.se	e section 5.2	- for broundbater informat	ia A	
0 -	0,2	- (or trooms and internal	<i>,</i> , , , , , , , , , , , , , , , , , ,	
		02 G-OBSERVED (DATE:)	D' POTENTAL	DALLEGED
DI M. M. SURFACE WATE DI POPULATION POTEN		04 NARRAZIVE DESCRIPTION	C :MONIAL	U ALEXED
-	•		•	
See	section 5.3	for surface wher intorn	ration	
		·		
OI C COMMAND	ONOFAR ILL	2 02 3 08 SERVED (DATE) OH NATURATIVE DESCRIPTION	MUSICA	O ALECED
63 POPULATION POTE	MINELY AS PECIED:	TC OF NOTTOLINE DESCRIPTION		
	Seo secti	on S.4 - Air Route		
•	266 26011	on so in in ivore		
ON TO D. PREEDPLOSE ON POPULATION POTE		02 DOSSERVED (DATE:	O SOTEME	D WTECED
			·	
	see section s.	5 - Fire and Explosion		
	•			
OR W.E. DIFECT CONT	IACTC. a.s.	OS (1) OGSERVED (DATE	E POTENTAL	O ALEGEO
63 FOPULATION POTE	MINITALLECTED ~ 6'00	(C) 04 MARRITINE DESCRIPTION		-
	10	5.6 - Direct Contact		•
	see section	C 3.0 MEG Girler		
	•			
OI OF F. CONTAINANT	TONOF SOL ~ 11/4	OF INTERIOR DESCRIPTION	O POTENTIAL	O WITECED
	Ford	- •	* . ***	
	see section	S.Z and Table 4-1		
•	-		: .	
OI ELOL DESKING WA	TERCONTAMENATION	OC DOSSERVED ADATE	ADDEDOL M	D ALEGED
63 POPULATION POT	ENTIRELY AFFECTED: 13,01	0 04 BURROUNE DESCRIPTION	A10.0.00	المستحدة المستحددة
	Sea section	n S. Z-Groundwater	•	
	100 SEO!10			
<u>.</u>				
41 ME HE WORKER D		OCENTRATIVEDESCRIPTION	MUDGLOS	D ALEGED
	See section.	5.6 - Direct Contact		
		polkers are employed at	the cite	

see section 5.2,5.4 and 5.6 for potential population

exposure.

SEPA

Dato=1207013(7-41)

POTENTIAL HAZARDOUS WASTESITE SITE INSPECTION REPORT

DI STATE OF STE HANDEN

PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCODUTS [IN 10981961501	_
E HUZARDOUS CONDITIONS AND HODENTS COMM	-
OI WILDWINGE TO FLORA CT DESCRIPTION	
Stressed vegetation observed on-site.	
OF EX CLUMCE TO FAINA OR DOSSESSED FOATE MOTENTAL DIALECED	
Darrage to fauna could occur through contact with contaminated	
still or by consuming contaminated flora.	
OT CL CONTINUENTION OF FOOD CHAIN OR CHOSSERVED POATE:	-
A LUISO LTING DESTROYM	
soil contaminants detected by FIT could potentially	
bioaccumulate in the food chain.	
OF THE LINSTABLE CONTAINABILITY OF WASTES OF FORWARD POLICE 4 12-91 1 TOTENTIAL C ALLEGED OF FORMATION POLICE 16,617 OF HARRATINE DESCRIPTION	\neg
CO POPULATION POTENTIALLY AFFECTED 10,1010 OF INSPIRATIVE DESCRIPTION	
sludge nixed with sawdust is stored in an open dumpoter. Dumpster was leaking during SII untreated wiste flowed onto the ground surface instead of draining into a 5,000 gallon 457	
OH IN DULLEETO OFFSTEPHOPERTY OF CHOSERVED PLATE	
frential for damage to off-site property through groundwater and air myration of contaminants detected on-site.	
groundwater and air myration of contaminants dollarted as-5:10	
OF INTERNATION OF SEWERS, STORM ORANG, WHITH OZ CHOSSERVED PAIRE	
westewater containing heavy metals is discharged to the sewer system algations of high metal content in wastemater discharged to sewers, however, fit has no documentation of sewer contamination.	•
fit has no documentation of sever contamination.	
61 D P. RLEGRANNUTHORIZED DUMPHS 02 DIOSSERVEN (DATE	
None documented	
65 DESCRIPTION OF ANY OTHER INDIME POTENTIAL OR ALEGED HAZAROS	
55-pallon orums, allegedly empty are stored in a shed that has a dirt floor, some drums were labelled flammable	
the a dist flow some down were labelled flowmable	
The desire floor, solving blockers and the second	
- Total (1001; soling of wind)	
IL TOTAL POPULATION POTENTIALLY AFFECTED: ~16, 6/2	
IL TOTAL POPULATION POTENTIALLY AFFECTED: ~16, 6/2. M. COLLMENTS	
IL TOTAL POPULATION POTENTIALLY AFFECTED: ~16, 6/2. M. COLLMENTS	
IL TOTAL POPULATION POTENTIALLY AFFECTED: ~16, 6/2.	
IL TOTAL POPULATION POTENTIALLY AFFECTED: ~16, 6/2. M. COLLMENTS	
RE TOTAL POPULATION POTENTIALLY AFFECTER -16, 6/2. M. COMMENTS Asbestos insulated piping was removed from the site in 1985. V. SOLFICES OF REGRESATION	
RETOTAL POPULATION POTENTIALLY AFFECTED: ~16,612. RECOMMENTS Asbestos insulated piping was removed from the site in 1985.	
M. COMMENTS Asbestos insulated piping was removed from the site in 1985. V. SOLANCES OF MEGRNATION	

O EDA	POTENTIAL	HAZARDOU	S WASTE SITE		LIDENTFICATION		
SEPA	SI PART 4- PERMIT A	TE INSPECT		ow.	1N 19819 \$ 1501		
L PERLIT INFORMATION .	17011111011111						
OI TYPE OF PERMIT ESUED	DE PENATHENDER	OT ONLE CANED	OH EUPPRATION DATE	STOWNOOD IS			
Om strawy	weknown.				•		
DA HPOES	aclA						
DC AIR	w/A						
OQ. ACRA	WA						
DE ACRAINTERMISTATUS WA							
OF. SPCCHUN	MA -			IDEM	loshwm 2		
M.G. STATE CHIE	00478	7/16/90	5 3191		dispose of 4toyd		
DH LOCAL BOWN	Milliamy]	1		क्ष्मिन केन्द्रि विद्या		
OL OTHER Group	MA		1	· · · · · · · · · · · · · · · · · · ·	ote-Watersh Paper Goodings		
DT HOHE	NA	<u></u>	<u> </u>	ar Wal	Wh Velley leastfill.		
IL SITE DESCRIPTION					1		
013.00	MOUNT 03 UNG OF	WEASURE OF	treatherit command	~~	oson-€R		
O A SURFACE MPOUNDMENT		1 -	LINCEHERATION		MA BUILDINGS ON SITE		
C DRUMS ABOVE GROUND TO SS	dallon drane-may be), UNOERGROUND IN 2. CHEMICAURINISIC				
DID TANK ABOVE GROUND	<u> </u>		D. BOLOGICAL		2		
E TANK BELONGROUND	5,000	<u>~ o</u>	E.WASTE OLPROCE	229G	OF AVENCY SITE		
- DE LINOPIL -		_	F. SOLVENT RECOVE		11/4		
DIC CANOFARM —		. 10	a other recycling H other	SPECOVERY			
	20 493	0	EUIIEI A	redg .			
OF COLLECTIS							
Paper coation	ng waste in to	readed u	ith alumin	این میا	fate, B-22 polymer		
and lime T	To shaha is :	mixed "	ith coulded	and 201	ed in a dumpster		
~61/2 ud3 cla	to its so and	1	1 1	UNU STOC	ישרניקריוניט איי		
014 90 21	ado 12 levinas	OIMONTA	ig. The wa	stewate	r is discharged		
to the se	ever system.	UST sta	ires coating	aask	prior to treatment		
W.CONTAINMENT -	· .				·		
91 CONTAINMENT OF MISTES, powered							
D A ADEQUATE SECURE	<u> </u>	- DC NA	ROOM STAUG	■0.kse	CIPE DESCRIPTION DIRECTORS		
confairer mere	locked adder	over flow	a croto the	am und	Dirtaio		
• •	•		•				
Prums, allegedy	empty are s	stored i	n a did	-floor She	以 .		
	•			-			
Y. ACCESSIBILITY							
OI WASTE EASU ACCESSME: TYE	. 010		•				
es convous	at fear day	92 ON W	curity or o	ردهت رو	stration exit;		
wask 15 stored	in-site in a	n open	dumpster.	•			
VL SOURCES OF INFORMATION A	سميز ميدستند 6 درس پيسز هه	*					
FIT and Sta	te file int	formation	 'A				
	• • • •						
SSI conducted on 4/17/91							

EAFORM 2070-1307-411

	POTE	NTIAL HAZARI	AW 2UCC	STESIT	E		TEPICATION
\$EPA		SITE INSPECT	ION REPO	RT		OI STAT	MOD INC ICAL
VLIA	PARTS-WATER	DEHOGRAPHIC	, AND EH	TRO KLE	HTAL DATA	IV	10981361501
EL DRINGCHO WATER SUPPLY							
OI TITLE OF OPENDA SUPPLY		es states				63:	ESTACE TO SEE
SURFACE	MEIT	ENONGERE	D AFFEC	TED L	HOHERONS		JI -
COLLENTY A.D	a.y.	A.G	9. (_	c ≰	٨.	1/2
HON-COLARINITY C.D	a pl	0.0	1:3	<u> </u>	F.D unkon	4 L	~
EL CROUNDWATER							
OI GOOD OWN TERESE HYCHTYD	~ .	-	•				1
CONFIGURATION DE TOTOS DE TOTO							
CC POPULATION SERVED BY COOLUMN TER "13,000 CHOCK TO NEAR ST DOWN CONTERVENT " IN							
04 DEPTH TO GROUNDWATER	S OPECTOR OF CA	OU OWEER ROW	04 0070170		OF SOUTH TE	1.0	ON SOLE SOUPCE ADUPTER
20	Assumed South	h	0f00x0	:	4 nikacu	ا ا	CIYES WIND
		`			1	1000	
Two municipal wi	of folks -	l is breaker	1/2	miles	southoust	of	the ste
and contains 7 well	C with dest	s mains for	on Gots	624	A second	41011	Seld is located
~3 miles southwest a	of the st	e and has	2 wells	OAR	187ftd	0.0	and the other is
207 St. And But well	hold deans	from Sanda	منهو نه	Q Roc	ideatal w	ellc	days from limesto
203 Ft - down Brith well	News V-400	116111 30010 90	1100000	CEMPEA	Dr. Sand	and	gravel
WYES COMMENTS PE	rmeable		#YES	CONTRACTO	as Goverde	سكور	may recharge
OND SO	ils	-	Ою	-	river	•	
N. SUFFACE WATER			1	L			
· · · · · · · · · · · · · · · · · · ·							
01 SUFFACE WATERESED							
PESERVOR RECREATED DEPORTED DEPORTS WATER SOURCE		IOIL ECONOMICALLI ANTRESOURCES	Y DC	COMBIENC	M. BOSTM	0	FICE CORPORT ASSET
CZ MYECTEDPOIDMALTAFECIED	100E3 OF WATER						_
KUE:					AFFECTE		DSTANCE TO SITE
	-					-	
				:	0	-	
				:	<u> </u>	-	
					0	-	
V. DEMOGRAPHICAND PROPER	TY INFORMATION	·					
61 SOTAL POPULATOR MINES		•		I	RE DISTRICTE TOPIC	NEST PO	WCO.
	TWO PO MELES OF SIT		(F) MLES OF	SITE	_		C.I.
A_6,000	<u>~12,700</u>	. a_	×13.000	-		30	H.
COMPRESSOR BRECHOS ACCIONATION	mia DioCarte		~		CST OFF WIE HAD		
			1	210101	•	_	
~4,	600				<u>~50</u>	11)
05 POPULATION WITH WONTY OF BET	Epra and more	and when the property with		**	-	~	
Moderately	populated 1	esidential,	:OMMOS	id a	rea		
•	Appendix				•		
1	- •			•			
			•				•
l							
1							

CANODA 2010-13 F-44

	POTENTIAL HAZAR	DOUS WASTE SITE	LIDENTIFICATION
\$EPA	SITE INSPECT		POLITE OF STERLOCK
VERA	PARTS-WATER DEMOGRAPHIA	CAND ENVIRONMENTAL DATA	IN: 1981961501
W DOWNOHUENTAL BEORNA	TION		<u> </u>
OI POWENSUTY OF ENGLIPPATED TO) { 0		
O A 10-4 - 10-4	*on/sec 0 8, 10** = 10** on/sec 0 6	C. 10-4 - 10-3 CHANCE \$ (D. CHENTER	R THAN 10 ⁻³ OWING
STATE STATE OF SECUCIONS			
O A SAPERU Emison	ZEABLE D B. RELATIVELY SUPERMEABLE OF The beautiful Control of the bea	E XC RELINELY PERSONNEL DE	D. VERT PERSEASE Community
XXX403€ वर्ग न्या ५३० वर्ग	04 DEPTHOF CONTAMENTED SOL ZO	es societ	
~30 💌	NUKUOMU W	MUKNOWY	
ON HEI PRECIMILATION	07 OF TEM STHOUGHNASTE	OLSLOPE DRECTIONOFSTE	SLOPE, TERRUHAVERAGESLOP
~3.68 m		— O NIA	~
OF PLOCO POTENTIAL	10	-	
STEISH 100 YEAR		erend construction that the subject of the subject	•
110STACE TO WETLACKS AND AND	~	EZESTANCE TO CHETCHE WET AT A TOWN	and the same
ESRUR€	опея	_23	<u>·</u> [#4]
MA M	2 73 m	BONCEREDSPECES_N	v/A
13LHOUSENVOIGT			•
DISTANCE TO:	RESOBITIVE AREAS HATIO	edustateparks. IG	ROLTRALIACS
COMECANORS	PEUL FORESTS, OR WLOUF	ERESERVES PAMEAGU	MO AGUNO
~ ~ 50ft	~ 50 4	tes cycknow	ω α <u>~3/4</u> ⊷
HOESOWTONOFSTENMENTON	110 SURYOUNCHIG TOPOCAVHIN		
	Refer to 4-mile	casius map in	Appendix A
5			•

M co. o co co consumou

FIT file information SSI conducted un 4/17/91

SEPA	PA	DI STATE OF S	8 KG ISOL	
& SAUCLES TAXEN	a masa	M SWATES SENT TO		ESTELLIEUDANE
SUPLETIFE	SWAD THEN			MESULTAMENALE
CROUNOMATER				
SUFFACE WATER		ORGANIC SOIL JAMPLES		
WASTE		Wadsworka/Alert Laboratories		
AR .		.4101 shuffel Drise, N.W.		
RUOF		North Canton, Ohio 44720		
SPLI				
SOL.	7	INORGANIC SOIL SAMPLES		available
VECETADON		Northern Laboratories		
on-ea		2400 Cumberland Drive Valparage, Indiana, 46383		
E FIELD MEASUREMENTS T	KEDA			
a ture	et conects			
OVA	No read.n	es above background		
radiation manifer	a	ings above background		
exhances or wass		is nutside normal range		
HCN monitox	3 4	dings on-site	·	
M.PHOTOGRAPHS AND MA	75			
OF SIPE HOUSE DANS		CHOSTORO Ecology & Environment	Chicag	0.16
878 040	Ecology & En	vironment, Inc Chicago, 12		
V.OTHERHEDOATACOU				·
None		• • • • • • • • • • • • • • • • • • •	- 2	
1				
1 .				
				•
			-	
YL SOURCES OF REGISTA	TION	LOS MORE WANTED		
		ded on 4/17/11		 -
		act of dated		
Labora	tory Analyt	ical Octa		
BY 100-12070-12/044				

≎ EPA	P	SITE INSPE	ARDOUS WASTE SITE CTION REPORT TER DIFORMATION		9819 6150 1
L CURRENT OWNER(S)			PARENT COMPANT		
ol sale	· k	A30+8MA-0EA	DE RAME	K	AD-EM B-OK
Matate Industr	اون ا	unknown	<i>N/A</i>	1	
OFFICET ACCESSES BANGO, MA		04 SC C00E	HOSTINGET ADDRESS # 0 Ama articles		11 500000€
wakaowa		YNKNOWN	1		
	DE STATE	27 52 CCCC€	15 COLA	PATE	14 27 COOE
Norwalk	CT	MUKUOWO	<u> </u>	} }	
01 EU-€ .		DZ D+8 NCJLINER	OR HATE		NOOM BOOK
•					
CLISTREET ACCESSIVA MANN, MA		04 SC CCOE	EM SAME O SEZEMOON FEETE OF		HISCOOL
∞ ⊘17	C& STATE	07 20 COOE	15014	PARE	14 20° COOE
orece NA	-	02 D+B ocuseA	NA		N39-1148+0 10
OF THEET WOMEDS PAR BANK OFF		04 SC 000E	10 STREET ACCRESS # & Ball #94 (m)		1150000
					_!
OCTY	DE STATE	OI D' COOE	गव्या	STATE	14 2P COOE
	<u> </u>				
NA		- 05 D+8 achees	NIA		OSO+S MULECA
STREET KONESSYA MANAGES		04.9C000€	14 STREET ACCRESS P. A. MARCHA		PISCOCCE
		· [
SCOTY	OS STATE	07 27 COOK	ri Cary	PARE	HZPCOXE
R. PREYICES OWNERS (Married		 	M. RELLTY OWNERS		
MENAGE	-	OZ D+BIRLINER	At the state of th		CE D+6 HUNCER
millen Indu	strice	unknown	MA		
COSTREET REPESSIVE MARKET		94.SCCCCCE	EDSTREET ACCPESSOR SHAPPE AND		04 SCCCOE
444 Back Aven	re South	uaknou		-	
SECTY	OESTAT	e or coor	CACAT	PASTATE	mancod .
New York	IVY				
MA STATE		OS BHENCAGER	NA-		450+8H7-063
		M-SC000E	OSPECTACOPESCA DALPREMA		
STREET HONESSYA BANKA, MILL			The state of the s		04.90000
WOOT	D6\$743	EO12PCCCE	ecor	PA STATE	M S-COCK
	· [1	1		
MINNE		02 D+B-MANGER	DI NAME		42 0+ 8 HJ-06A
unkne	W	1	NA		1
CONTRELEMENT AND		04.5C000E	COSPREED ACCRESS & A.		94 accore
	OOSTA	E 87 3000E	esory	- L	
prou		1		SIAN	as 52 COOK
W. G. C.		<u> </u>			<u> </u>
V. SOURCES OF INFORMATION					
FIT and	State Fil	e Informat	Λ 0C		
FIT UI cond	no byon	4/17/91	•		
		- ,			
W1.F07112878-13(F49		·			

0 500	ŧ	• • • • • • • • • • • • • • • • • • • •	DOUS WASTESITE	L DENTIFIC			
SEPA			TION REPORT TOR INFORMATION OF STATE				
		PANIE-UPDON					
L CURRENT OPERATOR		7	OPERATOR'S PARENT COLO		•		
Mat h 1.11 1 a	L	(219) S63-4181	Matcole Indu	2.	10.0 HLEA		
Matcok Walbash P	april (007)195	164 SC COOK	12 STREET ADDRESS P.O. A. M.		li3 SC CCCE		
			The state of the s	4.	1,32,002		
410 South Carr	on street	≖ler proces	N4 CRY	IIS STATE I	10 ZP COOE		
Wabash	10		Norwalk	CT			
ON YEARS OF OPERATION TOO	W40F0=68 -	-•			· · ·		
1985-present	Matcole Indu	stries.	·				
IL PREVIOUS OPERATOR	Ju-	and destinated	PREVIOUS OPERATORS'PA				
Wabash Pape	a Countings	CO-SHARES	MA		110+8 MARCA		
10) LIMES I WOMEN AND WAR	D-7,682	045CC00E	12 STREET ACCRESS P.O. And, And	-	13 50000€		
410 South Ca	moll street			<u> </u>			
Joe cours	prou	at a mark	14067	15 \$1436	14 2P COOE		
Wabash		1 46992	<u> </u>				
1965-1985	Mil	len Industries	·				
DIMME	0	CZ D+ S NE NGER	MA		110+8 HLEER		
Ford Meter	Box	unknown					
STATEST ADDRESS PAIN, M	94,41	01.5CCCCE	12 STREET ADDRESS P.O. Ave, MY	(m)	13 30000		
unknow	Vr						
CA CATY	4	ATE OF DIFFCOOL	14007	- 133125	NA ZIP CODE		
Unknow							
STEPS CHEMICA	-			_			
eraug.		ICZ D+B KLAGEA	10 MAGE	 	11 0+8 KL-46A		
Foundry -	unknown		NIA				
STREET ACCRESS PARA		OH SECONDE	12 STREET ADDRESS P.A. Aug My	Ka)	13 3CCCC		
				_			
OF CHA.	φs	ME OF STOOL	HORY	URO	H2PCCCE		
			-				
OF TELPS OF DEPATOR O	NUL OF COMERCUPES	O THE PERCO					
		<u> </u>		<u> </u>	<u> </u>		
IN. SOURCES OF INFORM	EATION pro quarte about		A~~~				
·							
1			•				
				·			
					•		
				-			
					_		
EPAPON 2010-13 (7-04)							

SEPA		POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART I - GENERATOR/TRANSPORTER INFORMATION			CATION HITE HA-BER 18/196/50/
LON-SITE CENERATOR					
91 male		NO-BHAMEA			
Matrok-Wabash	,	1 ~ × · · · ·			
410 South Car	11011 Street	P1 22 COCE		·	 .
Wabash	IN	46992			
A OFF-SITE CENERATOR(S)		02 D+8 MA-GEA	loraue		
NA			NA		05 0+8 K740EV
ESTREET ADDRESS P.S M. WOLLE.	3*.	04SCCCCE	COSTREET ADDRESS PA ILL MPC CO		04 SC COOK
SOF	ON STATE	of Street	SCIT S	OS STATE	07 ZP CCCE
MA NA		CO-BHASER	N/A		02 D+8 HAGER
DSTREET ADMESS P.A. M. MOV. or.		64 SC COOE	COSTREET ACCRESS P.D Sac MOL COL		04 9CCCC
a CITY	DA STATE	भ क्टळाड	os cuty	ON STATE	07 ZP CCCE
M_TRANSPORTER(S)					L
Wabash Valley f	he fuse Remo				OZ D+8 MJ-GER
BOX 406	• .	##SCCCCE	COSTREET ACCRESS / D. Inc. MP.L. and	•	94 8 C000E
Wabash	O STATE IN	46992	OF COLA	ON STATE	07 ZP CCCE
NA -	<u></u>	CO-SHL-GER	NA		03 D+8 XT-BEX
EDSTREET RECORDESS PARSON NOV.	=)	MECCOOL	STREET MOVEST PA DE MOCINE		01 900008
- acut	D4 STAR	E ST 25 COOK	otate -	- COLSTATE	07 2F CCCE
V. SOURCES OF INFORMATIO					<u> </u>
		information		· · · · · · · · · · · · · · · · · · ·	
	conduded o				·
-	· · · · · ·	nila			•
· 1		•			

ì

BT10-1300-1314

	POTENT	TAL HAZARDOUS WASTESITE		L DENTFICATION
SEPA	13	TE INSPECTION REPORT		OI STATE OF SITE MANDER
ALIV	PART 1	0-PAST RESPONSE ACTIVITIES	ļ	111/ 109819 61501
		······································		
L PAST RESPONSE ACTIVITY		CZ DATE	##O~	
O1 () A WATER SUPPLY O	1	CZ DATE	wace.	
~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	~/a			
	'			
O1 O B TEMPORARY MA	TER SUPPLY PROMOED	OZ DATE	BASENCY	
O4 DESCRIPTION	2.10			1
	חוא			 ,
OI D C PERMOREN	TER SUPRI PROVOED	CZ DATE	DKS-CY	
04 DESCRIPTION		-		
(NIA			i
OI D & SUED WORK		62 DATE	mescr	
O4 DESCRIPTION	•			
	NIA			l
		© DATE		
O1 D E CONTAMINATED O4 DESCRIPTION	SOC HENORED	es date	(DAGS)CT	
	NA			1
	ויון	· · · · · · · · · · · · · · · · · · ·	·	
OI OF WASTERSHOOM	ACED .	COATE	BKERCY	
O4 DESCRIPTION	م ار م			
	ML		-	I
OI O & WASTE DOPOS	36725#GE	02 DATE	. CO ACENCY	
O4 DESCRIPTION	مانہ			
	MA			
OI OH ON STERLER		CZ DATE	ELAGRICA	
O4 DESCRIPTION	1			
i	NA			
OI DINSTOCIO	H 79547964	62 DATE	DACOCT	
OL DESCRIPTION		42 Ords	u.coci	
	NA			1
OF DINEMAGE		62 DATE	****	
OF DESCRIPTION		42 DAVE	- GREET	
1	NA			
OI DEMSTURAS		er date		
O4 DESCRIPTION	•	**************************************		
-	NA	•		
0.00.000000		62 DATE		
OF DESCRIPTION	•	WUNE	. DANCE	
	NA	:	. =	•-
		65 DATE	-	
01 D M BIEIGECT	,	65 OKTE	, wast	
	NA			
ON CONCEPTION	.il A	65 DATE	. 634096	
	ΝJA			
		ISON 65 DYLE		
O1 C) O. BIEIGERCH O4 DESCRIPTION	DIONGENTHACE MULTER ONE	ROOM 65 DYIE	. COACEAC	ſ
W Contract	NIA			
	NA			
O1 DP. CUROFF THE	QESSIMP .	62 DATE	. WAGE	Y
04 DESCRIPTION	NA			
1	1,,			!
OI DO SUBSUFFICE	COROFF WEL	62 DATE	63/129/	Y .
04 DESCRIPTION	NA			
ìl	111			
MAJORA 2078-13(7-84)				

THE PERSON NAMED OF STREET

≎EPA	POTENTIAL HAZARDOUS WASTE SITE SITE MISPECTION REPORT PART 10-PAST RESPONSE ACTIVITIES	OFFICE MACENTAL OFFICE OF STATE OF STAT
BYAST RESPONSE ACTIVITIES PO-		
EM D A BARRER WALLS CONSTRUCTED SM DESCRIPTION	A CONTE	
C1 D & CUPRICOVERING C4 DESCRIPTION N		-
64 DESCRIPTION N		
64 D R CROWT CURTAN CONSTRUCTED N	A	
CY DESCRIBON 6-1 (D. A' BOLLON ZEVIED	& DATE	03 NOENCY
ed D w. gas control 64 description		
	A 314023	63 AGENCY
64 DESCRIPTION 64 DESCRIPTION	A CONTE	CO ACCORDA
	N/A	83 AGENCY
es D LACCESTOSTERESTRICTED O4 DESCRIPTION -	N/V	en resich
64 D 2 POPULION RELOCATED 64 DESCRIPTION	N/A -	CEL ACENCY
64 EX 1 ODER REJEDUR ACTIVITIES 04 DESCRIPTION	RME TO THE	COMMON TANK
•	•	to a man to the
;		
E corpora de managarante		•
IL SOURCES OF INFORMATION (Down		
FIT file inf	a Compatible of	
		-

DUDW 207413044



POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 11 - ENFORCEMENT INFORMATION

OF STATE OF STE MARCH 1 A. P. 2.196/50)

IL ENFORCEMENT INFORMATION

OI PAST RECULATORIAD FOR CONDINATION DI YES YOU

OR DESCRIPTION OF FEDERAL STATE, LOCAL RECOLLATORY/OFORCEMENT ACTION

Refer to Section 2-3 site History

M. SOURCES OF INFORMATION personal network of the time and professional

FIT File information

APPENDIX C

FIT SITE PHOTOGRAPHS

Walant Paper Coatings, Inc. SITE NAME:

PAGE

OF 16

U.S. EPA ID: 1N0981961501

TDD: F05-8802-004

PAN: FINO6625B

DATE: 4/17/91

TIME: 1330

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunny


~67°F

PHOTOGRAPHED BY:

D. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



closeup of sample SI

DATE: 4/17/91

TIME: 1330

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

> partly sunny ~67°F

PHOTOGRAPHED BY: O. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



perspective of sample SI; collected from an

area of blackened and stressed vegetation located approximately 15 feet

SITE NAME: -- Wabash Paper Coatings, Inc. PAGE 2 OF 16

U.S. EPA ID: 1N0981961501 TDD: FO5-8802-004 PAN: FINO6625B

DATE: 4/17/91

TIME: 1340

DIRECTION OF PHOTOGRAPH:

NW

WEATHER CONDITIONS:

partly sunny

~67°F

PHOTOGRAPHED BY:

0. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



closeup of Sample 52

DATE: 4/17/91

TIME: 1340

DIRECTION OF PHOTOGRAPH:


NW

WEATHER CONDITIONS:

~67°F

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



DESCRIPTION: perspective of sample 52; collected from an

area of stressed vegetation next to the manhole cover to the UST

SITE NAME:

Wahash Paper Coatings, Inc.

PAGE 3 OF 16

U.S. EPA ID: 1N0981961501

TDD: F05-8802-004

PAN: FINOG6 25B

DATE: 4/17/91

TIME: 1330

DIRECTION OF PHOTOGRAPH:


WEATHER CONDITIONS:

partly sunny

PHOTOGRAPHED BY: 0. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



DATE: 4/17/91

TIME: 1330


DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

> partly sunn ~67°F

PHOTOGRAPHED BY: D. Epstein

SAMPLE ID (if applicable):



DESCRIPTION: perspective of sample S3; collected from a public

of a liquid leaking from the northern edge of the refuse/sludge

SITE NAME:

Wabash Paper Coating PAGE 4 OF 15

U.S. EPA ID: /NO981961501 TDD: F05-8802-004

PAN: FINO66258

DATE: 4/17/91

TIME: 1407

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunny ~670F

PHOTOGRAPHED BY: O. Epstein

SAMPLE ID (if applicable): 54

DESCRIPTION:



loseup of sample 54

DATE: 4/17/91

TIME: 1407

DIRECTION OF PHOTOGRAPH:

N

WEATHER CONDITIONS:

partly sunny ~67°F

PHOTOGRAPHED BY: D.Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



perspective of sample Sy; collected from soil

beneath a crusty, yellow substance and stressed vegetation.

SITE NAME:

- Wabash Paper Coating

5 OF 16 PAGE

U.S. EPA ID: 100981961501

TDD: FOS-8802-04

PAN: F1 NO 6625B

DATE: 4/17/91

TIME: 1520

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

PHOTOGRAPHED BY: 0. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



doseup of sample SS

DATE: 4/17/91

1520 TIME:

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunny


~67°F

PHOTOGRAPHED BY:

D. Epstein

SAMPLE ID (if applicable): s 5

DESCRIPTION:



perspective of sample 55; collected from an

area of blackened soll and stressed vegetation west of the parking lot at the north end of the site:

SITE NAME: Mafcote - Wabash Paper Coating

PAGE 6 OF 16

U.S. EPA ID: 1N098/96/501 TDD: F05-8802-004

PAN: F1N0662

DATE: 4/17/91

TIME: 1452

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunny

PHOTOGRAPHED BY: 0. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:



closeup of sample 56

DATE: 4/17/91

TIME: 1492

DIRECTION OF PHOTOGRAPH: N

WEATHER CONDITIONS:

partly sunny ~67°F

PHOTOGRAPHED BY: 0. Epstein

SAMPLE ID (if applicable): 56

DESCRIPTION:



perspective of sample S6; collected

from an area of stressed vegetation approximately 20 feet southwest of the semitrations.

ITE NAHE: Wala;	sh Pap	er C	pating	Inc	PAGE 7	of 16	_
.S. BPA ID: IND 9							2
ATE:							
THE:							
DIRECTION OF PHOTOGRAPH:							
VEATHER CONDITIONS:				•		-	
PHOTOGRAPHED BY:							
SAMPLE ID (if applicable):							
DESCRIPTION:	C	loseup	of san	mple 57	unavaila	blo.	
due to							
DATE: 4/17/91				X X X X X X X X X X X X X X X X X X X		7M AMEN	
TIME: 16 45		M		NAZ	1		Des
DIRECTION OF PHOTOGRAPH:							
VEATHER CONDITIONS: Portly Sonny							
~67° F							
PHOTOGRAPHED BY: D. Epstein							
SAMPLE ID (if applicable):							(2)
DESCRIPTION:			Nation of	Y MARKE			
	Derspective	e of	Somple	reet, Wa	(bockg10	und)	
lesidenta	2 area;	184	middle 5	rest. Wa	bach. Ind	ana	

SI011(2/25/89)

SITE NAME: Wakash Paper Coating Inc

PAGE 8 OF 16

U.S. EPA ID: IND 981961501 TDD: F05-880 1-004

PAN: FI NO662

DATE: >4/17/91

TIME: > 1500


DIRECTION OF PHOTOGRAPH:

VEATHER CONDITIONS: > Puttly Sunny

> ~67°F

PHOTOGRAPHED BY: > D- Efstein

SAMPLE ID (if applicable):



DESCRIPTION: >

Front of building focing

Carroll Street

		FIELD PHOTOGRAPHY LOG SHEET	
SITE NAME:	Wabash	Paper Coatings Inc.	PAGE 9 OF 16
U.S. EPA ID:	1N0981961501	TDD: F05-8802-004	PAN: F1N06625B



DATE: 4/17/9/ TIME:	1500 DIRECTION OF PHOTOGRAPH: S	PHOTOGRAPHED BY: O. Epstein
	party sunny ~67°F	SAMPLE ID (if applicable):
DESCRIPTION:	Northern side of building; foregrow	nd has visible train tracks

FIELD	PHOTOGR.	APHY	LOG	SHEET

SITE NAME:

Wabash Paper Coating

PAGE 10 OF 16

U.S. EPA ID: IN 0981961501 TDD: FOS-8802-004

PAN: F/N06625B

DATE: 4/17-/91

TIME: 1530

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunry

~67°F

PHOTOGRAPHED BY:

D. Epstein

SAMPLE ID (if applicable):

DESCRIPTION:

sand for mixing with sludge are in foreground.

DATE: 4/17/91

TIME: 1935

DIRECTION OF PHOTOGRAPH: E


WEATHER CONDITIONS:

partly sunny ~67°F

PHOTOGRAPHED BY:

SAMPLE ID

maintenance shed; not is being repaired. DESCRIPTION:



0. Epstein (if applicable):

-			With the second second
FIELD	PHOTOGRAPHY	TOC	CHERT
- TULD	LUULUARAPHI	1.1117	SHEEL

SITE NAME: A Marte Walbash Paper Coating

PAGE 11 OF 16

U.S. EPA ID: 1N0981961501

TDD: F05-8802-004

PAN: F1 NO 66 25B

DATE: 4/17/91

TIME: 1350

DIRECTION OF PHOTOGRAPH:


WEATHER CONDITIONS:

partlyanny ~67°F

PHOTOGRAPHED BY:

D. Epster'n

SAMPLE ID (if applicable):



DESCRIPTION:

drain and pipes leading to underground storage tank.

DATE: 4/17/91

TIME: 1350

DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS:

partly sunny ~67°F

PHOTOGRAPHED BY: Metzas.0

SAMPLE ID (if applicable):

DESCRIPTION:



drain and pipes leading to underground storage tank.

manhole cover is entrance to underground storage tank

FIELD	PHOTO	GRAPHY	LOG	SHEET

Wabash Paper Coating
51501 TDD: SITE NAME:

PAGE |2 OF 15

U.S. EPA ID: 1N0981961501

F05-8802 -004

PAN: FINOGEZSB



DATE: 4/17/91 TIME: 1350 DIRECTION OF PHOTOGRAPH: NE	PHOTOGRAPHED BY: 0.Epstein
WEATHER CONDITIONS: gastly Sungy ~67°F	SAMPLE ID (if applicable):
DESCRIPTION: drain and pipe leading from treatment sink in side	building to underground
Storage tank Bi-level portion of building is warehouse (st	orage area for papercores and finished
products	· · · · · / /

SITE NAME: Wakoash fact Coahing TDD: FOL-8802-007

PAGE 13 OF 16

PAGE 13 OF 16



DATE: 4/17/91 TIME: 1500 DIRECTION OF PHOTOGRAPH: NW PHOTOGRAPHED BY: 0.565/90.

SAMPLE ID (if applicable):


DESCRIPTION: property boundary of Matrote - Walbash lapar Coating is west of the seam - trailers. Dict accost road leads from Carcoll 5t. to parking lot on north side of Matrote - Walbash

FIELD PHOTOGRAPHY LOG SHEET			
SITE NAME:	Wabash Pape	ic Coating	PAGE 14 OF 16
U.S. EPA ID: 1N098		TDD: F05-8802-004	PAN: F/ N066 25 B



DATE: 4/17/9/ TIME: 1500 DIRECTION OF PHOTOGRAPH: E	PHOTOGRAPHED BY: 0. Epstein
WEATHER CONDITIONS: partly sungy ~67°F	SAMPLE ID (if applicable):
DESCRIPTION: view of Mafcote Wahash facing east show	ving refuse dumpster and
wooden pallets.	

FIELD PHOTOGRAPHY LOG SHEET				
SITE NAME:	- Wabash	Paper Coating	PAGE /5 OF 16	
U.S. EPA ID:	1N0981961501	TDD: F05 - 8802-004	PAN: F/N06625B	



DATE: 4/17/91 TIME: 1530 DIR	ECTION OF PHOTOGRAPH:	PHOTOGRAPHED BY: 0. Epsterio
WEATHER CONDITIONS: party sung	2670F	SAMPLE ID (if applicable):
DESCRIPTION: Maintenance shed is	on the south, Debris in	foreground is from roof repair
of the mainknance shed.		

FIELD PHOTOGRAPHY LOG SHEET				
SITE NAME:	Waloush	Pages Coating		PAGE 16 OF 16
U.S. EPA ID:	1N0981961501	TDD:	F05-8802-004	PAN: F1N066258



DATE: 4/17/91 TIME: 1530 .	DIRECTION OF PHOTOGRAPH:	PHOTOGRAPHED BY: 0. Epstein
WEATHER CONDITIONS: partly sunny	~67°F	SAMPLE ID (if applicable):
DESCRIPTION: parking lot fa	aing drum storage shed.	

APPENDIX D

U.S. EPA TARGET COMPOUND LIST AND
TARGET ANALYTE LIST
QUANTITATION/DETECTION LIMITS

Contract Laboratory Program Target Compound List Quantitation Limits

			SOI L
COHPOUND	CAS ‡	VATER	SLUDGE
Chloromethane	74-87-3	10 ug/L	10 ug/K g
Bromomethane	74-83-9	10	10
Vinyl chloride	75-01-4	10	10
Chloroethane	75-00-3	10	10
Kethylene chloride	75-09-2	5	5
Acetone	67-64-1	· 10	5
Carbon disulfide	75-15-0	S	5
1,1-dichloroethene	75-35-4	5	5
1,1-dichloroethane	75-34-3	5	5 5 5
1,2-dichloroethene (total)	540-59-0	5	5 .
Chloroform	67-66-3	5 5	5
1,2-dichloroethane	107-05-2	5	5
2-butanone (MEK)	78-93-3	10	10 -
1,1,1-trichloroethane	71-55-6	5	Ś
Carbon tetrachloride	56-23-5	5	5
Vinyl acetate	108-05-4	10	10
Bromodichloromethane	75-27-4	5	5
1,2-dichloropropane	78-87-5	5	5
cis-1,3-dichloropropene	10061-01-5	5	5
Trichloroethene	79-01-6	5	5
Dibromochloromethane	124-48-1	5	5
1,1,2-trichloroethane	79-00-5	5	· 5
Benzene e	71-43-2	5	. 5
Trans-1,3-dichloropropene	10061-02-6	. 5	5
Bromoform	75-25-2	5	5
4-Hethyl-2-pentanone	108-10-1	10	10
2-Rexanone	591-78-6	10	10
Tetrachloroethene	127-18-4	5	5
Tolene	108-88-3	5	5
1,1,2,2-tetrachloroethane	79-34-5	\$	5
Chlorobenzene	108-90-7	5	5 5 5 5 5
Ethyl benzene	100-41-4	5	5
Styrene	100-42-5	5	5
Xylenes (total)	1330-20-7	5	5

Table A
Contract Laboratory Program
Target Compound List
Semivolatiles Quantitation Limits

		•	SOIL SEDIMENT
COMPOUND	CAS \$	VATER	SLUDGE
Phezol	108-95-2	10 ug/L	330 ug/Kg
ois(2-Chloroethyl) ether	111-44-4	10	330
2-Chlorophenol	95-57-8	10	.330
l,3-Dichlorobenzene	541-73-1	10	330
l,4-Dichlorobenzene	106-46-7	10	330
Benzyl Alcohol	100-51-6	10	330
1,2-Dichlorobenzene	95-50-1	10	330
2-He thylphenol	95-48-7	10	330
bis(2-Chloroisopropyl) ether		. 10	330
4-Hethylphenol	106-44-5	10	330
N-Nitroso-di-n-dipropylamine		10	330
Hexachloroethane	67-72-1	10 .	330 -
Nitrobenzene	98-95-3	10	330
Isophorone	78-59-1	10	330
2-Fitrophenol	88-75-5	10	330
2,4-Dimethylphenol	105-67-9	10	330
Benzoic Acid	65-85-0	50	1600
bis(2-Chloroethoxy) methane	111-91-1	10	330
2,4-Dichlorophenol	120-83-2	10	330
1,2,4-Trichlorobenzene	120-82-1	10	330
Naphthalese	91-20-3	10	330
4-Chloroaniline	106-47-8	10	330
Hexachlorobutadiene	87-68-3	10	300
4-Chloro-3-methylphenol	59-50-7	10	330
2-Eethylnaphthalene	91-57-6	10	330
Bezachlorocyclopentadiene	77-47-4	10	330
2,4,6-Trichlorophenol	88-06-2	10	330
2,4,5-Trichlorophenol	95-95-4	50	1600
2-Chloronaphthalene	91-58-7	10	330
2-Hitroaniline	88-74-4	50	1600
Dimethylphthalate	131-11-3	10	.330
Acenaphthylene	208-96-8	10	330
2,6-Dinitrotoluene	606-20-2	10	330
3-Nitroaniline	99-09-2	50	1600
Acenaphthene	83-32-9	10	330
2,4-Dinitrophenol	51-28-5	50	1600
4-Nitrophenol	100-02-7	50	1600
Dibenzofuran	132-64-9	10	330
2,4-Dinitrotoluene	121-14-2	10	
Diethylphthalate	84-66-2	10	330 330
4-Chlorophenyl-phenyl ether	7005-72-3	10	330 330

Table A
Contract Laboratory Program
Target Compound List
Semivolatiles Quantitation Limits

		• ,	SOIL SLUDGE
COHPOUND	CAS #	VATER	SEDIMENT
Fluorene	86-73-7	10 ug/L	330 ug/Kg
4-Nitroaniline	100-01-6	50	1600
4,6-Dinitro-2-methylphenol	534-52-1	50	1600
M-nitrosodiphenylamine	86-30-6	10	330
4-Bromophenyl-phenylether	101-55-3	10	330
Bexachlorobenzene	118-74-1	10	330 ·
Pentachlorophenol	87-86-5	50	- 1600
Phenanthrene	85-01-8	10	330 ·
Anthracene	120-12-7	10	330
Di-n-butylphthalate	84-74-2	10	330-
Fluoranthene	206-44-0	10	330
Pyrene	129-00-0	10	330
Butylbenzylphthalate	85-68-7	10	330
3,3°-Dichlorobenzidine	91-94-1	20	660
Benzo(a)anthracene	56-55-3	10	330
Chrysene	218-01-9	10	330
bis(2-Ethylhexyl)phthalate	117-81-7	10	330
Di-n-octylphthalate	117-84-0	10	330
Benzo(b)fluoranthene	205-99-2	10	330
Benzo(k)fluoranthene	207-08-9	10	330
Benzo(a)pyrene	50-32-8	10	. 330
Indeno(1,2,3-cd)pyrene	193-39-5	10	330
Dibenz(a,h)anthracene	53-70-3	10	330
Benzo(g,h,i)perylene	191-24-2	10	330

Table A
Contract Laboratory Program
Target Compound List
Pesticide and PCB Quantitation Limits

			SOIL SEDIHENT
COMPOUND	CAS #	VATER .	SLUDGE
alpha-BHC	319 -84 -6	0.05 ug/L	8 ug/Kg
beta-BHC	319 -85 -7	0.05	8
delta-BHC	319-86-8	0.05	8
gamma-BHC (Lindane)	58 -89- 9	0.05	8
Beptachlor	76-44-8	0.05	8
Aldrin	309-00-2	0.05	8
Beptachlor epoxide	1024-57-3	0.05	8
Endosulfan I	95 9-9 8-8	0.05	8
Dieldrin	60-57-1	0.10	16
4,4'-DDE	72-55-9	0.10	16
Eadrin	72-20-8	0.10	16
Endosulfan II	33213-65-9	0.10	16
4,4'-DDD	72-54-8	0.10	16
Eadosulfan sulfate	1031-07-8	0.10	16
4,4'-DDT	50-29-3	0.10	16
Methoxychlor (Mariate)	72-43-5	0.5	80
Endrin ketone	53494-70-5	0.10	16
alpha-Chlordane	5103-71-9	0.5	80
gamma-chlordane	5103-74-2	0.5	80
Toxaphene	8001-35-2	1.0	160
AROCLOR-1016	12674-11-2	0.5	80
AROCLOR-1221	11104-28-2	0.5	80
AROCLOR-1232	11141-16-5	0.5	80
AROCLOR-1242	53469-21-9	0.5	80
AROCLOR-1248	12672-29-6	0.5	80
AROCLOR-1254	11097-69-1	1.0	160
AROCLOR-1260	11096-82-5	1.0	160

Table A (Cont.)

CONTRACT LABORATORY PROGRAM TARGET ANALYTE LIST (TAL) INORGANIC DETECTION LIMITS

		Detection Limits			
Compound	Procedure	Water (µg/L)	Soil Sediment Sludge (mg/kg)		
aluminum	ICP	200	40		
antimony	furnace	60	2.4		
arsenic	furnace	10	2		
barium	ICP	200	40		
beryllium	ICP	5	1		
cadmium	ICP	5	1		
calcium	ICP	5,000	1,000		
chromium	ICP	10	2		
cobalt	ICP	50	10		
copper	ICP	25	5		
iron	ICP	100	20		
lead	furnace	5	. 1		
magnesium	ICP	5,000	1,000		
manganese	ICP	15	3.		
mercury	cold vapor	0.2	0.008		
nickel	ĪCP	40	8		
potassium	ICP	5,000	1,000		
selenium	furnace	. 5	1		
silver	ICP	10	2		
sodium	ICP	5,000	1,000		
thallium	furnace	10	. 2		
tin	ICP	40	8		
vanadium	ICP	50	10		
zinc	ICP	20	4		
cyanide	color	10	2		

3767:1

APPENDIX E

WELL LOGS OF THE AREA OF THE SITE

DIVISION OF WATER DEPARTMENT OF NATURAL RESOURCES, STATE OF INDIANA STATE OFFICE BUILDING INDIANAPOLIS, INDIANA 46204

WL-1

State Form 35680

Telephone

317-232-4160

1063

Con While house of the or relief france well the control of the second

WATER WELL RECORD

Non-responsive, well locations

E OF WELL OWNER and/or BUILDING CONTI	RACTOR
Well Owner Container Corp. of America	Address Wabash, Indiana
Building Contractor	Address
of Well Drilling Contractor:Peerless-Mid	rest. Inc.
	26, Granger, DK 46530
Orilling Equipment Operator: John Ko	llar
L INFORMATION (RESCREENING OF	Originally drilled by others 1939
of well:31'	Date well was completed: Rescreening - 6-27-84
eter of casing or drive pipe:54"	Total Length: 33 '6"
eter of liner (if used):	Total Length: .040"
eter of Screen: 12" Length: 7'	8" .040" 6" Slot Size:‡4
of Well: Drilled Gravel Pack	Driven Other
f Well: For Home For Ind	ustry X For Public Supply Stock Stock
	Rev. Rotary Jet Bucket Rig cand development of well after rescreening ound to water level)
Test: Hours TestedRate	
ing Test: Hours Tested 8 Rate	between static irrel and water 178 g.p.m. Drawdown 9 (t. levi at end of sest)
	Signature P.J. Williams R. J. Williams
•	7 100

Control of the Contro

DIVISION OF WATER RESOURCES INDIANA DEPARTMENT OF CONSERVATION 311 WEST WASHINGTON STREET INDIANAPOLIS, INDIANA



WATER WELL RECORD

Non-responsive, well locations
CC
De
or or
Non-responsive, PII
Name of Well Drilling Contractor: 1 10 1915 17 1812
Address: R3 Wabash Ind.
Name of Drilling Equipment Operator:
INFORMATION ON THE WELL
Completed depth of well: 102 ft. Date well was completed: Jan 28.
Diameter of outside casing or drive pipe:
Diameter of inside casing or liner: Length:
Diameter of Screen: Length: Slot size:
Type of Well: Drilled Gravel Pack Driven O Other
Use of Well: For home For industry For public supply Stock
Method of Drilling: Cable Tools Rotary Rev. Rotary Jet Driven
Static water level in completed well (Distance from ground to water level) 4 ft.
Bailer Test: Hours tested Rate g.p.m. Drawdown ft. (Difference between
Pumping Test: Hours testedRate
Signature Warmal It . The
Date 100 28 1941

WATER WELL LOG				2
FORMATIONS (Color, type of material, hardness, etc.)	From	То	Topo. Map:) () Cull at El. of grnd. surface at Depth to bedrock: Well Log processed by:	70 Z
Class	0	39	Map:	on-responsive, well
2 mid *3'	39	42	finp:) () ci. ().5 grnd. surface to bedrock: bg processed by	
limestone	12	102	rfac	
	ļ		by:	
	<u> </u>		at well	
		<u> </u>	A T	
			0 R	
<u> </u>	-	7		
	<u> </u>		7,75	
			c w	
			Loo. Court	
			Loo. napepted w/o Courthouse Loc. Field Located Placed in Master	
			pted e Lo ated Mas	
		٠.	7 / 0	
	<u> </u>		o varifiantion By Roman By Well Log File	
	<u> </u>	<u> </u>	E Bad	
	<u> </u>			
		-	You - Date Date Date	
REMARKS:	-	-	No No	
			- 6	
		ن ن عرب		
INSTRUCTIO	NS .	ί	•	,

This Water Well Record form is designed to record the most essential data concerning a water well. We request that you be as accurate as possible in recording this information as it may be of great assistance in the clanning and development of new water supplies.

An accurate location of the well is equally as important as an accurate well log. Please include all information possible in the space provided for well location.

As specified in Chapter 6 of the Lots of 1959, a copy of this report must be similted within thirty days after the completion of a well to the Division of Water Resources, Indiana Department of Conservation, 311 West Washington Street, Indianapolis, Indiana.

ACCEPTED TO

 \hat{i}

DIVISION OF WATER RESOURCES
INDIANA DEPARTMENT OF CONSERVATION
609 STATE OFFICE BUILDING
INDIANAPOLIS, INDIANA 46209
MElrose 3-6757

WATER WELL RECORD



Non-responsive, well locations

Name of owner Non-responsive, PII
Name of Well Drilling Contractor: Empire Helland Lung Capacition
Address: 27 Halaut St Habash
Name of Drilling Equipment Operator: Mr. Homen J. Blass
INFORMATION ON THE WELL
Completed depth of well: 96 ft. Date well was completed: 326 1966
Diameter of outside casing or drive pipe: 4 inch Length: 18 feet
Diameter of inside casing or liner:Length:
Diameter of Screen: Length: Slot size:
Type of Well: Drilled 🛇 Gravel Pack 🗌 Driven 🗍 Other
Use of Well: For home 🛭 For industry 🗌 For public supply 🗍 Stock 🗍
Method of Drilling: Cable Tools 🛛 Rotary 🗋 Rev. Rotary 🗍 Jet 🗍 Driven 🗍
Static water level in completed well (Distance from ground to water level) 45 ft.
Bailer Test: Hours tested / Rate 400 g.p.# Drawdown 0 ft. (Difference between
Pumping Test: Hours tested 5 Rate 600 g.p.# Drawdown 0 ft. level at end of test)
Signature Harrin J. Bly
Date March 3, 1960

WATER WELL LOG			
FORMATIONS (Color, type of material, hardness, etc.)	Fron	To	COUNTY Topo Map: Like Topo Map: Like The Courthouse located Field located Acc. W/o verification
Scoun clay Sand with little grand #61' Sand very lard packed #32' Limetone	0	2	Map: Nap: Nap:
Sand with little grand "61"	2	63	classified of located verification
Sand very lard packed #32'	63	.95	rica cate kiri
Limeitore	95	96	ed d
			By L By L
· · · · · · · · · · · · · · · · · · ·			RE R
715 /			FOR Date Date Date
620			B. AD
			ADMINISTRATIVE
		<u> </u>	STRAS
		<u> </u>	
			USE
			AC S AC E N S C N
	:		0000
		-	NAT.
	<u></u>	-	Ground Depth to Bedrock Aquifar
			ind a h to cock
•			
REMARKS:			levationbedrockelevation.
its riuts.			
		-	p 5 7 7

INSTRUCTIONS

This Water Well Record form is designed to record the most essential data concerning a water well. We request that you be as accurate as possible in recording this information as it may be of great assistance in the planning and development of new water supplies.

An accurate location of the well is equally as important as an accurate well log. Please include all information possible in the space provided for well location.

As specified in Chapter 6 of the Acts of 1959, a copy of this report must be similtied within thirty days after the completion of a well to the Division of Water Resources, Indiana Department of Conservation.

DIVISION OF WATER DEPARTMENT OF NATURAL RESOURCES, STATE OF INDIANA STATE OFFICE BUILDING INDIANAPOLIS, INDIANA 46209

WATER WELL RECORD



County in which well was a Congressional township:
Describe in your own words
or distinctive landmarks:
Name of owner Non-responsive, PII
Name of Well Drilling Contractor: Heliyi ? Sins inc
Address: 5418 Linishu Bled Thateen, Sub
Name of Drilling Equipment Operator:
INFÓRMATION ON THE WELL
Completed depth of well: 61 ft. Date well was completed: 7-17-70
Diameter of outside casing or drive pipe: 4" Length: 55
Diameter of inside casing or liner:Length:
Diameter of Screen: Length: Slot size:
Type of Well: Drilled Gravel Pack Driven Other
Use of Well: For home For industry For public supply Stock
Method of Drilling: Cable Tools Rotary Rev. Rotary Jet Driven
Static water level in completed well (Distance from ground to water level)ft.
Bailer Test: Hours tested Rate g.p.m. Drawdown ft. (Difference between static level and water Pumping Test: Hours tested Rate 5 C5.p.m. Drawdown ft. level at end of test)
Signature Militia C. McCo

0000

J

INSTRUCTIONS

This Water Well Record form is designed to record the most essential data concerning a water well. We request that you be as accurate as possible in recording this information as it may be of great assistance in the planning and development of new water supplies.

An accurate location of the well is equally as important as an accurate well log. Please include all information possible in the space provided for well location.


REPARKS:

As specified in Chapter 6 of the Acts of 1957, a copy of this report must be submitted within thirty days after the completion of a well to the Division of Water

DIVISION OF WATER RESOURCES
16 INDIANA DEPARTMENT OF CONSERVATION
311 WEST WASHINGTON STREET
INDIANAPOLIS, INDIANA
WATER
WATER

De

OI



-responsive, well loca

Name of Well Drilling Contractor: Roam Self- Roam Self- Name of Drilling Equipment Operator: Log Carly
Address:
Name of Drilling Equipment Operator:
INFORMATION ON THE WELL
Completed depth of well: 105 ft. Date well was completed: 9-8-6/
Diameter of outside casing or drive pipe:
Diameter of inside casing or liner:Length:
Dizmeter of Screen:Length:Slot size:
Type of Well: Drilled Gravel Pack Driven Other
Use of Well: For home B For industry For public supply Stock
Method of Drilling: Cable Tools Rotary Rev. Rotary Jet Driven
Static water level in completed well (Distance from ground to water level) 65 ft.
Bailer Test: Hours tested / Rate / g.p.m. Drawdown / o ft. (Difference between
Pumping Test: Hours testedRateg.p.m. Drawdownft. level at end of test)
Signature Vilbur Mouser
Date

WATER WELL LOG			
FORMATIONS (Color, type of material, hardness, etc.)	Fron	To	COUNTY:(Topo. Map: El. of grn Depth to b Well Log p
Yellow Clay	0	32	20 20 20 1
Linestone	32	105	Walkers.
			Makada Wakada nd. surface at well bedrock: processed by: An
		Non-re	sponsive, well locations
			_
		1	
	<u> </u>		
	2		
	56		
REMARKS:	BE		
REMARAS:	1	4	
	100	D.	
INSTRUCTION	s	13/2	`

This Water Well Record form is designed to record the most essential data concerning a water well. We request that you be as accurate as possible in recording this information as it may be of great assistance in the planning and development of new water supplies.

An accurate location of the well is equally as important as an accurate well log. Please include all information possible in the space provided for well location.

As specified in Chapter 6 of the Acts of 1959, a copy of this report must be submitted within thirty days after the completion of a well to the Division of Water Resources, Indiana Department of Conservation, 311 West Washington Street, Indianapolis, Indiana.

Lacorporate

MISHAWAKA, INDIANA

☐ TEST				
₩ PERMANENT		Job N	o HICS	10
WEIL LOG No. (FL) Echach		tyt	iebesh	
Owner General Tire: Melber Company		shipl		
		tion		
Location	Indiara			
From Land Description ft. East and		ಮ of SW	Comer o	f Section
From Street or Room				
River - I Forth of old #3 well		·		
	Parties.	Dopte to	GROUND I	EVEL Statle
FORMATICE CHIMD — DESCRIBE FULLY	Supr	Sotion of Stratum	ed Statum	Water
		4		
<u> </u>		1	1	
Erec Indy Clay	:	5	F	
Fire Brown Seni Clean		15	10	
1 22 2700 000 0000	<u>-</u> -			
Oer ≥nd and Gravel	<u>E</u>	17	2	
Clear travel and Sand	r	21	. 4	
hade Iley Seni - Gravel	2	23	2	
Cie Coerse Send	2	31	8	14
		<u> </u>	6	
Eroc Line Rock	<u> </u>	31}	0	
•	<u> </u>			
	-			
	 -	- 		
				
				·
	<u> </u>			
	 			
			ļ	<u> </u>
·	1			
			1	
	<u> </u>			<u> </u>
- Cable Too	d C fine	_ ☐ Jetti	ng	
Pipe left in hole 15 15 (200 below ground and 150 abo			-	
13 35 feet perior decome was 12 - 800		_		
Date Started		illyell page	<u> </u>	

APR 1965
APR

DIVISION OF WATER RESOURCES INDIANA DEPARTMENT OF CONSERVATION 609 STATE OFFICE BUILDING INDIANAPOLIS, INDIANA 46209 MELTOSE 3-6757

STREMMEL & IIIL WL-7

Phone 981-1191
LaFontaine, Indiana

WATER WELL RECORD

C7/C0CC00/US
Non-responsive, well locations
Cong
Desc
et U S Road 24. Well in brout of builders about
10' W. of - NE comes and en about I from front
Name of owner: Cashway Lumber Company Address: Marion, Indiana
Name of Well Drilling Contractor: Stremmel & Hill
Address: 105 West Kendall Street LaFontaine, Indiana 46940
Name of Drilling Equipment Operator: Cecil Siders
INFCRMATION ON THE WELL
Completed depth of well: 115 ft. Date well was completed: 3/25/65
Diameter of outside casing or drive pipe:Length:
Diameter of inside casing or liner: he Length: 21:
Diameter of Screen: Length: Slot size:
Type of Well: Drilled KX Gravel Pack Driven Other
Use of Well: For home For industry For public supply Stock
Method of Drilling: Cable Tools IX Rotary Rev. Retary Jet Driven
Static water level in completed well (Distance from ground to water level) 30 ft.
Bailer Test: Hours tested _ Rate 15 g.p.m. Drawdown _ ft. (Difference between
static level and water Pumping Test: Hours tested 2 Rate 16 g.p.m. Drawdown 0 ft. level at end of test)
Signature STERMIEL - HILL
Date spril 12, 1965 by Jenn Thill
FOR WELL LOG SPACE USE REVERSE SIDE OF THIS SHEET

WATER WELL LOG			· · · · · · · · · · · · · · · · · · ·
FORMATIONS (Color, type of material, hardness, etc.)	From	То	COUNTY: Topo Nap: Well log cl Courthouse Field locat Acc. w/o va
Fill	0	3_	W/o
Very hard yellow limestone	3	25	ap: og classified located located /o verificati
medium hard grey linestone	25	40	Elca Elca
soft blue water-bearing stone	40	115	classified classified verification
			By By
			FOR ADMINISTRATIVE (Well driller does not Date 1/3/6 3- Da
			111c
		-	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	<u> </u>		not fill
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			FIT S OF THE S
	-		R F R F F C C C C C C C C C C C C C C C
	-		oppel of the state
		<u> </u>	Oround el Dapth to Dedrock e Aquifer e
	<u> </u>		
REMARKS:			lavation bedrock elevation elevation
torsum.		<u> </u>	
			133
			11171

This Water Well Record form is designed to record the most essential data concerning a water well. We request that you be as accurate as possible in recording this information as it may be of great assistance in the planning and development of new water supplies.

INSTRUCTIONS -

An accurate location of the well is equally as important as an accurate well log. Please include all information possible in the space provided for well location.

As specified in Chapter 6 of the Acts of 1959, a copy of this report must be submitted within thirty days after the completion of a well to the Division of Water Resources, Indiana Department of Conservation.

DIVISION OF WATER RESOURCES INDIANA DEPARTMENT OF CONSERVATION 311 WEST WASHINGTON STREET INDIANAPOLIS, INDIANA

WATER WELL RECORD

WATER WELL LOG			<u> </u>
ORMATIONS (Color, type of material, hardness, etc.)	From	To	COUNTY: Topo. M El. of Depth t
full + Lander Class		10	
Sandy park oftand 418'	10	27	1 (3-1
will the said 432'	4.7	60	aurface ock:
Will Azzad Frank Agt	100	6-4	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
			Ti i
			1 []
			772
			(Well D
		1	P. P.
		-	ADMINISTRATIVE USE Driller does not fi P RGE Loc. accept Courthouse Field Locat Placed in N
	 	 	RATIVE does n RGE. Loc. a Courth Field Placed
	<u> </u>		anot bed Lo
	 		
	 	-	1 - ^ 1 -
-	 -		-i - °
	-		
	 	-{	fication log File
·	 	ļ	
		 	Date Date
EMARKS:	-		-
Aux wanta - ort statu	Trac	46	No
Int Williamph Then work	_		
JI /			

INSTRUCTIONS

This Water Well Record form is designed to record the most essential data concerning a vater well. We request that you be as accurate as possible in recording this information as t may be of great assistance in the planning and development of new water supplies.

An accurate location of the well is equally as important as an accurate well log. 'lease include all information possible in the space provided for well location.

As specified in Chapter 6 of the Acts of 1959, a copy of this report must be submitted ithin thirty days after the completion of a well to the Division of Water Resources, Indiana epartment of Conservation, 311 West Washington Street, Indianapolis, Indiana.

LAYNE-NORTHERN COMPANY

lacorporcied

WELL NO. 1

mishawaka, indiana

ERMANENT		Job No. H11,393 County Habash
L LOG No Seith fl CITY Wabash		
er Indiana bater Corp.		Township Noble
		Township Noble Section Solve
ation		Indiana State
From Land Description	ft. East and	ft. North of SW Corner of Section.
From Street or Road SSS 4. of Y		

		1 NATURAL		
FORMATION FOUND — DESCRIBE FULLY	Dopth to Top of Strutum	Dopth to Sotion of Stratum	Thickness of Strutum	Starte Water Lovel
Brown Clay	Э	3	5	
Srawn Clay with Sand and gravel	3	17	12 ,	-
Grey Clay with Sand and gravel	17	43	23	
රුලු \$4ක්	(40)	46	6 ,	
Brown Gravel	46	48	2	
Grey Tlay with sand and grovel	48	23	35	
	E3	115	36	
Grey Crove!	119	133	14	
Brown Glay	133	137	4	
Grey Gravel	137	206	6 ē	41'
.				
				<u> </u>
				
				1
•				
inch diameter hole drilled by [] Cabie I			 	٠

Date Stated -3/29/65-

Finished 4-37-65

Schoon

DRILLER

Pipe extends <u>0</u> feet	Shore smund level	Job :	Not11393
Ground	Level	Location from Street 395° N. of Yankee Ed.	
Ground	18461	100° H. of Foli	
		CountySabash	
		Township Moble	
		Section 33	
		Pipe Tally	Velded Dreniel x
		Bottom	11*5**
-	← 12 Bla	ack Steel Pipe lbs. per Foot	11' 3"
		ins. per 100c	11'9"
			11.6 2.
		. · · · · · · ·	m, fü.
	-		13" 5"
			10° 7
Dopth 160'6"	Load soal ex egainst pipe		10.6.
	ro e		19*8"
163°3	В	lank Tube	95 11"
ept.ii	Steel Div	e Shoo Yes	13*3*
	424°	Cook	11/8
	*HME.	Screen Top	13, 194
	Opening 8	Total	163'3"
	=		_
203*			· · · · · · · · · · · · · · · · · · ·
Depth	Botton 41'	LAYNE TUBULAR I	TELL No. Smith #1
Static Level	116	For Indiana mater c	•
at	GPH pumping level	VARAGE, IN	
after	hours		·
Driller	2	LAYNE NORTH	•
Date Finished	4-30-6)	MISHAWAKA,	INDIANA
Not drawn to so		DRAWN BY APPROVED BY DATE	DRAWING NO.

the set william after

		all the second of the second	The state of	-
ipe extends 1 feet ab	i , , , ,		्रीक ४	°- <u>×11,523</u>
	ove Browne Tever.	Location from		
Ground	Lovel	100° W of		
		County Ha	bash	
		Township K	oble	
		Section		· · · · · · · · · · · · · · · · · · ·
		Pipe	Tally	Welded Thousands
			Bottom	12'2"
		ck Steel Pipe bs. per Foot		10'4"
				12*
	-			11' 3"
	•			10" 6"
			· ·	11'2"
	Load seal exp	ended.	•.	10197
Depth 145	against pipe			12. 4
				12*3
Depth 147'		lank Tube Ho		11'6"
	3	Shoe Yes	•	11'47
	42 ft. of	Cook	Ton	u.
2.	Opening #		Тор	10/5"
			Total	147'
				•
Depth	Botton		 -	
Static Level		LAYNE	TUBULAR WE For	LL No
1420	GPH .		TER CORP.	SHITH FIELD
runpeu <2	mping level	1	Wabash, In	D.
after hou	•			
BrillerSchoon		LAYNE	NORTHER	IN GO. ING.
Date Finished 10-	22-65		AWAKA,	INDIANA
Not drawn to scale	from Ground Level	DRAWN BY APPROVED BY DATE		, DRAWING NO.

Andre Language 116 th character cans a constitution of the constit

RGE._6-

MISHAWAKA, INDIANA		WELL NO. 2			
TEST		Wall523			
PERMANENT - Saith Field	Job No. 2-11523				
WELL LOG No. 2 CITY Wabash		omy			
Owner_Indiana iistar Corp		-			
	Sec	tion_	1603		
Location		de			
From Land Descriptionft. East and	ft. No	rth of SW	Corner of	of Section	
From Street or Road 190° West of Tankas R4.					
800° Forth of Wolf 3d.					
	Dopth to		GROUND	LEVEL Storie	
FORMATION FOUND — DESCRIBE FULLY	Top of Strutum	Dopth to Bottom of Stratum	el Stratum	Water Level	
Brosm Clay	3	6	5		
Brown Clay with eard and grovel	6	15	•		
	15	71	56		
Grey clay with send and grave! Red Clay	71	79	8		
		113	74		
Grey Clay with sand and gravel	74	113			
Grey sacé gravel	:13	137	74	44	
]	
				1	
				<u> </u>	
				 -	
• • • · · · · · · · · · · · · · · · · ·		<u> </u>		<u> </u>	
	1	į	1		
	1			 	
		 	 	 	
			<u> </u>	<u> </u>	
· · · · · · · · · · · · · · · · · · ·					
				{	
•				1	
-	1		-	+	
	_	 	-	 	
	ł	1	1	1	

Date Started 9-27-65

Pipe left in hole

12

Finished 17-72-65

167' - 40' Cook screen

inch diameter hole drilled by lacktriangle Cable Tool lacktriangle Rotary lacktriangle Jetting

Schoon

DRILLER